

A5, A5 Cabriolet, S5 2017 FLUID CAPACITY CHART

22 July 2015



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A5 Coupe quattro (8T35G9) Manual	2.0L TFSI 220 hp (CAED) 4.5L (4.8 qt) <u>Audi Oil Spec**</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd (0B2) 4.5L (4.7qt) <u>Oil PN</u> G 055 532 A2*	N/A	Front F/Drive <u>New Fill:</u> 1.1L (1.2 qt) <u>Oil PN</u> G 055 190 A2* Rear F/Drive (0BC) <u>New Fill:</u> 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2*	10.0 L (10.5 qt)***	1.0 L (1.1qt) (approximately) <u>Audi Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750 *	<u>Refrigerant</u> Use only R134a 550 g ± 15 g (19.5 oz. ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity</u> Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) <u>Fluid PN</u> G 052 300 A2*	4.5L (4.8 qt) <u>Fluid PN</u> G 052 164*
A5 quattro (8F752A) Cabrio	2.0L TFSI 220 hp (CPMB) 4.5L (4.8 qt) <u>Audi Oil Spec**</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	N/A	8-Spd Tiptronic (0BK/OBL) <u>New Fill:</u> 8.6 L (9.0 qt) <u>Change:</u> 3.6 - 4.0L (3.8 - 4.2 qt.) <u>Oil PN</u> G 060 162 A2	Front F/Drive <u>New Fill:</u> 1.0L (1.1qt) Transfer Case <u>New Fill:</u> 1.0L (1.1 qt.) <u>Change:</u> 0.8L (0.84 qt.) <u>Oil PN</u> G 055 145 A2				
A5 Coupe quattro (8T352A)			Rear F/Drive (0BD) <u>New Fill:</u> 1.0L (1.1 qt) <u>Oil PN</u> G 052 145 S2*					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.

A5, A5 Cabriolet, S5 2017 FLUID CAPACITY CHART

22 July 2015

Truth in Engineering



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
S5 Coupe quattro (8T3549) Manual	3.0L V6 333 hp (CTUB) 6.8L (7.2 qt) <u>Audi Oil Spec**</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd (0B4) 3.8L (4.0 qt) <u>Oil PN</u> G 052 911 A2*	N/A	Front F/Drive <u>New Fill:</u> 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2*	12.0 L (12.6 qt)***	1.0 L (1.1qt) approximately <u>Audi Brake Fluid</u> <u>Specification:</u> Use new fluid only.	<u>Refrigerant</u> Use only R134a 550 g ± 15 g (19.5 oz. ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity</u> Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) <u>Fluid PN</u> G 052 300 A2*	4.5L (4.8 qt) <u>Fluid PN</u> G 052 164*
S5 Coupe quattro (8T354Y) Cabriolet quattro (8F754Y)	(Same as above)	N/A	7-Spd DSG (0B5) <u>New Fill:</u> 7.0 - 7.5L (7.3 - 7.9 qt) <u>Change:</u> 6.7L (7.0 qt) approx. <u>Oil PN</u> G 052 529 A2*	Transfer Case <u>New Fill:</u> 4.35L (4.5 qt) <u>Oil PN</u> G 055 532 A2* Rear F/Drive (0BC / 0BD) <u>New Fill:</u> 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2*	Rear F/Drive (0BE) <u>New Fill Gear Oil:</u> 1.4 L (1.4 qt) <u>New Fill ATF:</u> 1.4 L (1.4 qt) Rear F/Drive (0BF) <u>New Fill Gear Oil:</u> 0.95 L (1.0 qt.) <u>New Fill ATF:</u> 0.85 L (0.9 qt.) <u>Oil PN</u> G 052 145 S2* Gear oil G 055 515 A2* ATF	FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750 *	(Same as above)	(Same as above)

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.