



# Technical Service Bulletin

---

## 17 MIL on; whistling noises from engine compartment (DTC P2279 and/or P0507)

17 17 80 2040644/7 February 14, 2017. Supersedes Technical Service Bulletin Group 17 number 17-79 dated January 19, 2017 for reasons listed below.

Model(s)	Year	VIN Range	Vehicle-Specific Equipment
A6, A7, A8	2013 - 2016	All	4.0 TFSI

## Condition

REVISION HISTORY		
Revision	Date	Purpose
7	-	Revised <i>Required Parts and Tools</i> (Updated part number)
6	01/19/2017	Revised <i>Warranty</i> (Updated time units and Claim Type)
5	03/18/2016	Revised <i>Required Parts and Tools</i> (Added retaining clip, o-ring, coolant additive, and distilled water)

- A metallic whistling or grinding sound is heard from the engine compartment when the vehicle is at idle speed.
- The sound usually only occurs when the engine is warm.
- The MIL is sporadically on.

The following DTCs are stored in the engine control module (ECM), J623 (address word 0001):

- **DTC P2279** (Intake air system leak)
- **DTC P0507** (Idle control system rpm higher than expected)

## Technical Background

A leak in the crankcase breather module (pressure regulating valve) can cause this condition.

## Production Solution

Fabric reinforced internal membrane of crankcase breather module.

# Technical Service Bulletin

---

## Service

1. Perform both of the following checks before proceeding:
  - Compare the sound of the vehicle to the sound in the video located at:  
<https://audi-external.kzoplatform.com:443/swf/player/311>  
(Figure 1).
  - Open the filler cap to check whether the sound is affected when the filler cap is open.



*Figure 1. QR code for viewing the video with a QR code reader on phones and tablets. Alternatively, the video can be accessed through computer internet browsers at the link provided in this bulletin.*

2. If the sound of the vehicle matches the sound in the video **and** the sound is affected when the filler cap is opened, replace the oil separator breather module.



# Technical Service Bulletin

## Warranty

<b>Claim Type:</b>	<ul style="list-style-type: none"> <li>• 110 up to 48 Months/50,000 Miles.</li> <li>• G10 for CPO Covered Vehicles – Verify Owner.</li> <li>• If vehicle is outside any warranty, this Technical Service Bulletin is informational only.</li> </ul>		
<b>Service Number:</b>	1726		
<b>Damage Code:</b>	0050		
<b>Labor Operations:</b>	<b>For A8 and S8:</b>		
	Oil separator breather remove +reinstall	1753 1971	20 TU
	Air intake distributor remove + reinstall	2446 1921	470 TU
	<b>For S6 and S7:</b>		
	Oil separator breather remove + reinstall	1753 1971	20 TU
	Air intake distributor remove + reinstall	2446 1921	600 TU
	Additional labor for adjustment of ACC, top view camera, and night vision, if necessary based on vehicle equipment	See Elsa	See Elsa
	<b>For RS7:</b>		
	Oil separator breather remove +reinstall	1753 1971	20 TU
	Refrigerant drain + fill	8703 1700	60 TU



# Technical Service Bulletin

	Air intake distributor remove + reinstall	2446 1923	690 TU
	Additional labor for adjustment of ACC, top view camera, and night vision, if necessary based on vehicle equipment	See Elsa	See Elsa
<b>Diagnostic Time:</b>	GFF – Checking and clearing fault codes included in existing labor operations	0150 0000	10 TU
	Road test prior to service procedure	0121 0002	10 TU
	Road test after service procedure	0121 0004	10 TU
	Technical diagnosis at dealer's discretion (Refer to Section 2.2.1.2 and Audi Warranty Online for DADP allowance details)		
<b>Claim Comment:</b>	As per TSB #2040644/7		

All warranty claims submitted for payment must be in accordance with the *Audi Warranty Policies and Procedures Manual*. Claims are subject to review or audit by Audi Warranty.

## Required Parts and Tools

Part Number	Part Description	Quantity
079103542E	Oil separator	1
079129717J	Gasket intercooler left	1
079129717K	Gasket intercooler right	1
N 90442501	Retaining clip	2



# Technical Service Bulletin

---

N 90489801	Retaining clip	2
N 90409501	Retaining clip	2
079145818	Gasket throttle body	1
079145417B	Gasket recirculation valve	2
WHT 001011	O-ring	1
G 013A8J1G	Coolant additive	1
Outside material	Distilled water (obtain locally)	As needed (Max \$10.00)

## Additional Information

All parts and service references provided in this TSB (2040644) are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

©2017 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites without the prior expressed written permission of the publisher.