Executive Service



2014 Q5

Engine	Part	Part Number	Quantity
	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
2.0L TFSI: CPMB	Drain Plug Gasket	N 0138157	1
	Air Filter >> 04.11.2013	8R0133843K	
	Air Filter 04.11.2013 >>	8K0133843M	1

Engine	Part	Part Number	Quantity
	Oil Filter	06J115403Q	1
2.0L TFSI Hybrid: CHJA	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
Crijit	Drain Plug Gasket	N 0138157	1
	Air Filter	8R0133843K	1

Engine	Part	Part Number	Quantity
	Oil Filter	06E115562A	1
3.0L V6: CTUC	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use O-ring:	8K0133843 N 90964301	1

Engine	Part	Part Number	Quantity
	Oil Filter	06E115562A	1
3.0L V6: CTUD	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use O-ring:	8K0133843 N 90964301	1

6-15-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

Executive Service

Engine	Part	Part Number	Quantity
	Oil Filter	059198405	1
3.0L TDI: CPNB	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.4L (6.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use O-ring:	8K0133843D N 909643901	1

2014 Q5

Miscellaneous	Part	Part Number	Quantity
	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8R1955425B	1
Miscellaneous	Passenger's Wiper Blade (Right)	8R1955426B	1
Miscellaneous	Battery	000915105CCDSP	1
	Battery	000915105CDDSP	1
	Battery	000915105CEDSP	1
	Battery	000915105CFDSP	1

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle.

You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the CAR function button > Service interval display > Reset oil change interval or CAR function button > Car systems* control button > Servicing & checks > Service intervals > Reset oil change interval.

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

Executive Service



2014 Q5



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Do not exceed the time interval for the next service, even if the vehicle mileage is low.



Do not reset the display between oil changes, otherwise the display will be incorrect.

 The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-15-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

Q5 SUV quatro 2.0 TFSI 220 hp (CPMB) 8-Spd Tiptronic (DBK/OBL) Front F/Drive New Fill: 3.6 L (4.9 qt) 1.0 L (1.0gt)*** Electromechanical 1.0 L (1.1qt) Refrigerant Use only R134a 4.6 L (8RB52A) 4.6 L (4.9 qt) New Fill: 3.6 L (4.9 qt) OII PN (0SK/OBL) 01 PN (3.6 4.0 qt) 01 PN (3.6 4.0 qt) 01 PN (3.6 4.2 qt) 01 PN (3.6 4.2 qt) 0.0 L (1.1qt) 1.0 L (1.1qt) Use only R134a 4.6 L Q5 SUV quattro 3.0 L V6 272 hp (CTUC) Refill 3.6 4.1 (2.2 qt) 0.6 L (7.2 qt) 0.0 L PN (3.8 4.2 qt) 1.0 L (1.1qt) 12.0 L (12.7qt)*** Use new fluid only. 01 Capacity & PN For Denso SUV quattro 6.8 L (7.2 qt) 01 PN G 050 145 A2* 01 PN G 052 145 S2* 12.0 L (12.7qt)*** 01 Capacity & PN For Denso Fluid PN B 000 750* G 052 300 A2* SUV quattro 3.0 L TO V 6 SAE SW-40, SAE SW-4	Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield Headlight Fluid
(8RB52A) Aut Coll Spectrum (W 502 00) New Fill: (9.0 cf.) OII PN (9.0 cf.) OII PN (9.0 cf.) OII PN (9.0 cf.) Rev Fill: (9.0 cf.) Question (9.0 cf.) Refrigerant 01 (1.0 cf.) Refrigerant 01 (0BD) Refrigerant 01	SUV	2.0 TFSI 220 hp (CPMB)	Tiptronic	New Fill:	10.0 L (10.5qt)***	Electromechanical		Use only R134a 630g ± 15g	4.6 L (4.9 qt. <u>Fluid PN</u> G 052 164*
SAE 0W-40 3.6-4.0 L (3.8-4.2 qt.) (UBD) (UBD) OII OII OII Capacity & PN For Denso Q5 SUV quattro quattro 3.0L V6 272 hp (CTUC) OII PN G 060 162 A2* 1.0L (1.1qt) 12.0 L (12.7qt)*** FMVSS 116 DOT 4 or SAE J 1703 OII Capacity & PN For Denso (8RB57A) 6.8 L (7.2 qt.) Transfer Case 1.0 L (1.1 qt.) OII PN G 055 145 A2* 0II PN G 055 145 A2* 12.0 L (12.7qt)*** Fluid PN B 000 750* G 052 300 A2* VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-40, SAE 5W-40, SAE 5W-40, SAE 5W-40, SAE 5W-40, SAE 5W-30 or SAE 0V-40 0II PN G 055 145 A2* AdBlue@ Tank C 0 55 145 A2* Fluid PN B 000 750* G 052 300 A2* VU quattro Quattro Quattro Quattro Use synthetic oil SAE 5W 30 or SAE 0V-40 AdBlue@ Tank C 0.55 145 A2* V V (8RB5VA) 6.4 L (6.8 qt.)	(8RB52A)	Audi Oil Spec** VW 502 00 Use synthetic oil SAE 5W-40,	8.6 L approx. (9.0 qt.) <u>Refill</u>	G 052 145 S2* Rear F/Drive			Fluid Specification:	Refrigerant Oil Use a PAG oil	0.002.101
SUV quattro (CTUC) OII PN G 060 162 A2* OII PN G 052 145 S2* Dot 4 or SAE J 1703 DOT 4 or SAE J 1703 DOT 4 or SAE J 1703 (8RB57A) 6.8 L (7.2 qt.) Transfer Case 1.0 L (1.1 qt.) Transfer Case 0 055 145 A2* 6 052 145 S2* 6 052 300 A2* G 052 300 A2* W 502 00 Use synthetic oil SAE 5W-40, SAE 5W 40, SAE 5W 40,	Q5	SAE 0W-40	(3.8-4.2 qt.)		12.0 L (12.7at)***		FMVSS 116		
Audi Oil Spec**: 1.0 L (1.1 qt.) Oil PN G 052 300 A2* WW 502 00 Oil PN G 055 145 A2* B 000 750* B 000 750* Use synthetic oil SAE 5W-40, SAE 5W-40, SAE 5W-40, SAE 5W-40 SAE 5W-30 or SAE 5W-40 AdBlue® Tank Refrigerant Q5 3.0 L TDI V6 Use only R134a G 030 ± 15g (22.2 ± 0.5 oz.) Use only R134a Quattro 6.4 L (6.8 qt.) Image: Same synthetic oil Image: Same synthetic oil Oil Capacity & PN For Denso Mudi Oil Spec**: WW 507 00 Image: Same synthetic oil Image: Same synthetic oil Image: Same synthetic oil Use synthetic oil Image: Same synthetic oil Image: Same synthetic oil Image: Same synthetic oil Image: Same synthetic oil Use synthetic oil Image: Same synthetic oil Image: Same synthetic oil Image: Same synthetic oil Image: Same synthetic oil Use synthetic oil Same synthetic oil Image: Same synthetic oil Use synthetic oil Image: Same synthetic oil Image	quattro	(CTUC)	G 060 162 A2*						
SUV quattro 240 hp (CPNB) Use only R134a 630g ± 15g (22.2 ± 0.5 oz.) (8RB5VA) 6.4 L (6.8 qt.) ISO Standard 22241-1 Oil Capacity & PN For Denso Audi Oil Spec**: VW 507 00 Use synthetic oil SAF ETWL 40 Oil Capacity & PN For Denso For Denso		VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or	1.0 L (1.1 qt.) <u>Oil PN</u>					G 052 300 A2*	
Audi Oil Spec**: Oil Capacity & PN VW 507 00 Soft Standard Use synthetic oil Only fill with filling Soft Standard 150 cc +/- 10 cc	SUV quattro	240 hp (CPNB)				23.0L (6.0 gal)****		Use only R134a 630g ± 15g	
Use synthetic oil device VAS6542 & 150 cc +/- 10 cc		VW 507 00				22241-1			
SAE 5W-30 or SAE 0W-40 (5.1 ± 0.3 oz.)		SAÉ 5W-40, SAE 5W-30 or				device VAS6542 & holding device		150 cc +/- 10 cc (5.1 ± 0.3 oz.)	

Audi (

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

** Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

**** Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2 for warranty repairs, 2.5 gal (10.0L) GUS 052 910 A3 for maintenance services.

© 2013 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
SQ5 quattro (8RB5CA)	3.0L V6 354 hp (CTUD) 6.8 L (7.2 qt.) Audi Oil Spec**: VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBK/OBL) <u>New Fill:</u> 8.6 L approx. (9.0 qt.) <u>Refill</u> 3.6-4.0 L (3.8-4.2 qt.) <u>Oil PN</u> G 060 162 A2* Transfer Case 1.0 L (1.1 qt.) <u>Oil PN</u> G 055 145 A2*	Front F/Drive New Fill: 1.0L (1.1qt) 0.9 L (0.9 qt.) <u>Oil PN</u> G 052 145 S2* Rear F/Drive (0BC) 0.9L (0.9qt) <u>Oil PN</u> G 052 145 S2*	12.0 L (12.7qt)***	Electromechanical	1.0 L (1.1qt) (approximately) <u>VW Brake</u> <u>Fluid</u> <u>Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	Refrigerant Use only R134a 630g ± 15g (22.3 ± 0.5 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity & PN For Denso 150 cc +/- 10 cc (5.1 ± 0.3 oz.) G 052 300 A2*	4.6 L (4.9 qt) <u>Fluid PN</u> G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

** Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

© 2013 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

Q5 Hybrid - 2014 FLUID CAPACITY CHART 01 Aug 2013

Truth in Engineering

Audi

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield 8 Headlight Fluid
Q5 Hybrid quattro (8RB5GA)	2.0 TFSI 211 h.p. / 245 h.p. total power output (CHJA) 4.6L (4.9 qt) <u>Audi Oil Spec**</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBWA) <u>New Fill:</u> 8.6 L approx. (9.0 qt.) <u>Refill</u> 4.0L (4.2 qt.) <u>Oil PN</u> G 060 162 A2* Transfer Case 1.0L (1.1 qt.) <u>Refill</u> 0.8 L (0.8 qt.) <u>Oil PN</u> G 055 145 A2*	Front F/Drive New Fill: 1.0L (1.1qt) <u>Refill</u> 0.9 L (0.9 qt.) G 052 145 S2* Rear F/Drive (0BC) 0.9L (0.9qt) <u>Oil PN</u> G 052 145 S2*	10.0 L (10.5qt)***	Electromechanical	1.0 L (1.1qt) (approximately) <u>VW Brake</u> <u>Fluid</u> <u>Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	Refrigerant Use only R134a 840g ± 20g (29.6 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity & PN For Denso 200 cc +/- 20 cc (6.7 ± 0.6 oz.) G 052 300 A2*	4.6 L (4.9 qt) <u>Fluid PN</u> G 052 164*

**Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

© 2013 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.