



Engine	Part	Part Number	Quantity
2.0L: CCTA	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	1K0129620D	1

Miscellaneous	Part	Part Number	Quantity
Miscellaneous	Pollen Filter (20K Only)	1K1819653B	1
	Pollen Filter (20K Only)	TBD	1
	Driver's Wiper Blade (Left)	8U1955425	1
	Passenger's Wiper Blade (Right)	8U1955426	1
	Rear Wiper Blade	8K9955425	1
	Battery	000915105CCDSP	1
	Battery	000915105DEDSP	1
	Battery	000915105DGDSP	1

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle.

You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the **CAR** function button > **Systems** or **Car systems** > **Servicing & checks** > **Service intervals** > **Reset oil change interval**.



Note

- Only reset the oil change indicator when you have completed an oil change.
- If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.

Q3 - 2015 FLUID CAPACITY CHART

Final July 31, 2014

Audi
Truth in Engineering



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Final Drive	Cooling System	Brake System	A/C System	Windshield Fluid
Q3 FWD - Auto (8UB)	2.0L 200 hp (CCTA) 4.6L (4.9 qt.) <u>Audi Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd Tiptronic (09M) <u>New Fill:</u> 7.0 L (7.4 qt) <u>Oil PN</u> G 055 025 A2*	Capacity included with transmission	10.0L (10.5 qt)***	1.0 L (1.1qt) (approximately) <u>Audi Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703	<u>Refrigerant</u> Use only R134a <u>Refrig. Capacity</u> 520 +/- 15 g (18.3 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a	4.5L (4.8qt) <u>Fluid PN</u> G 052 164*
Q3 quattro (8UB)		6-Spd AWD Tiptronic (09M) <u>New Fill:</u> 7.0 L (7.4 qt) <u>Oil PN</u> G 055 025 A2* Bevel Box <u>New Fill:</u> 0.9 L (1.0 qt) <u>Oil PN</u> G 052 145 S2	Rear Final Dr (0AY) 0.95L (1.0 qt) <u>Oil PN</u> G 052 145 S2* Haldex Clutch <u>New Fill:</u> 0.85L (0.9 qt) <u>Change:</u> 0.7L (0.7qt) <u>Oil PN</u> G 055 060 A2*	10.0L (10.5 qt)***	<u>Fluid PN</u> B 000 750 *	<u>Oil PN & Capacity</u> 1) For Delphi use 110 cc +/- 10 cc (3.7 ± 0.3 fl. oz.) 2) For Denso use 90 cc +/- 10 cc (3.0 ± 0.3 fl. oz.) G 052 300 A2* G 052 154 A2*	
<p>For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb. * Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information. ** Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard. *** Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.</p>							

© 2014 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.