A4,allroad, Ultra 2017 FLUID CAPACITY CHART Update 10/10/16 Truth in Engineering



| Vehicle (Sales Code) | Engine Oil approx. qty. w/filter change | Auto Trans | Final Drive | Cooling System | Brake System | A/C System | Windshield & Headlight Fluid |
|-------------------------|--|---------------|--------------------|--------------------|---------------------|---------------------------------|------------------------------------|
| A4 | 2.0L TFSI 252 hp | 7-Spd | Rear F/Drive | 10.0L (10.5 qt)*** | 1.0 L (1.1qt) | Refrigerant | w/o headlight |
| FWD | (CYMC) | S-tronic | (0DB) | 10.02 (10.0 40) | (approximately) | Use only R134a | wash |
| | (01) | (0CK/0CL) | 0.67L - (0.7 qt.) | | (5,44,5,) | 590 ± 15g | 4.8L (5.1 qt.) |
| (8W25NG) | 5.2L (5.49 qt) | (| | | | $(20.8 \pm 0.5 \text{ oz.})$ | |
| , | (1, | Automatic | Rear F/Drive | | VW Brake Fluid | , | |
| | Audi Oil Spec** | 3.5L (3.6 qt) | (0D2) | | Specification: | | |
| | VW 502 00** | (1, | 0.85L - (0.89 qt.) | | | Refrigerant Oil | Fluid PN |
| | Or | Oil PN | , , , , | | Use new fluid only. | Use a PAG oil | G 052 164* |
| | VW 504 00** | G 055 529 A2 | Oil PN | | | with R134a | |
| | | | G 052 190 A2* | | FMVSS 116 DOT 4 | | |
| | Use synthetic oil | Manual: | | | or SAE J 1703 | | |
| | SAE 5W-40, | 3.8L (4.0 qt) | Rear F/Drive | | | Oil PN & Capacity | |
| | SAE 5W-30 or | | (0D3) | | | For Denso use: | |
| | SAE 0W-40 | <u>Oil PN</u> | 0.95L (1.0 qt) | | | | |
| A4 | | G 052 549 A2 | | | Fluid PN | 110 cc ± 10 cc | |
| quattro | | | <u>Oil PN</u> | | B 000 750* | $(3.8 \pm 0.3 \text{ fl. oz.})$ | |
| (0)4(051)() | | | G 052 145 S2* | | | | |
| (8W25NY) | | | | | | G 052 300 A2* | |
| allroad | | | | | | | |
| (8WH5NY) | | | | | | | |
| (OVVIDINI) | | | | | | | |

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

© 2016 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.

A4,allroad, Ultra 2017 FLUID CAPACITY CHAR Update 10/10/16 Truth in Engineering



| Vehicle (Sales Code) | Engine Oil approx. qty. w/filter change | Auto Trans | Final Drive | Cooling System | Brake System | A/C System | Windshield & Headlight Fluid |
|---------------------------------|---|--|--|--------------------|---|---|--|
| A4 FWD (8W25MG) ULTRA B-CYCLE | 2.0L TFSI 190 hp (DBPA) 5.2L (5.49 qt) Audi Oil Spec** VW 508 00** Use synthetic oil SAE 0W-20 | 7-Spd S-tronic (0CK) Automatic 3.5L (3.6 qt) Oil PN G 055 529 A2 Manual: 3.8L (4.0 qt) Oil PN G 052 549 A2 | Rear F/Drive (0DB) 0.67L - (0.7 qt.) Rear F/Drive (0D2) 0.85L - (0.89 qt.) Oil PN G 052 190 A2* Rear F/Drive (0D3) 0.95L (1.0 qt) Oil PN G 052 145 S2* | 10.0L (10.5 qt)*** | 1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750* | Refrigerant Use only R134a 590 ± 15g (20.8 ± 0.5 oz.) Refrigerant Oil Use a PAG oil with R134a Oil PN & Capacity For Denso use: 110 cc ± 10 cc (3.8 ± 0.3 fl. oz.) For Sanden use: 100 cc ± 10 cc (3.3 ± 0.3 fl. oz.) G 052 300 A2* | w/o headlight wash 4.8L (5.1 qt.) Fluid PN G 052 164* |
| | | | | | | | |

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

© 2016 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.