

Technical Service Bulletin

SUBJECT:			No:	TSB-19-23-001
CORRECTION TO AUTOMATIC TRANSAXLE DATA LIST REFERENCE TABLE FOR F6AJA & W6AJA - SERVICE MANUAL REVISION				February 2019
				2007-16 Outlander
CIRCULATE TO:	[] GENERAL MANAGER	[X] PARTS MANAGER		[X] TECHNICIAN
[X] SERVICE ADVISOR	[X] SERVICE MANAGER	[X] WARRANTY PROCESSO	OR	[] SALES MANAGER

PURPOSE

This TSB updates the Automatic Transmission section of the affected Service Manual, to correct information in the diagnosis data list reference table for automatic transmissions F6AJA and W6AJA.

AFFECTED VEHICLES

• 2007 - 2016 Outlander

AFFECTED SERVICE MANUAL

• 2007 - 2016 Outlander Service Manual, Group 23-Automatic Transmission



Please make the indicated changes to the 2007 - 2016 Outlander Service Manual, Group 23-Automatic Transaxle -> CVT -> Diagnosis <S-AWC> -> Data List Reference Table.

Item No.	Inspection item	Inspection requirement	Normal condition
18 2-6 brake solenoid pressure	2-6 brake solenoid	Gear range: 1st, 3rd - 5th	0 MPa
	pressure	Gear range: 2nd or 6th	1.58 MPa
19 Low clutch solenoid pressure	Gear range: 5th or 6th	0 MPa	
	pressure	Gear range: 1st - 4th	1.58 MPa
20 3-5 reverse clutch SOL. pressure	Transmission range: N	0 MPa	
	pressure	Transmission range: R	1.58 MPa
21 High clutch solenoid pressure	High clutch solenoid	Gear range: 1st - 3rd	0 MPa
	pressure	Gear range: 4th - 6th	1.58 MPa
22 Lock up difference pressure	Lock up difference pressure	Lock-up engaged (warmed up and constant speed driving)	0.8 MPa
		Lock-up disengaged	-0.4 MPa «Correct»
23	Line pressure	Depending on engine torque and A/T conditions	0 - 1.58 MPa <lnc< td=""></lnc<>
24 Target gear	Target gear	Gear range: 1st	1 <pre>closerrect></pre>
		Gear range: 2nd	2 Approximately 1 A
		Gear range: 3rd	3 0 A 1 - 3 A
		Gear range: 4th	1-3A 40A
		Gear range: 5th	5
		Gear range: 6th	6 Cerrest
25 L/U & Low & Rev. brake SOL. monitor		Lock-up engaged (warmed up and constant speed driving)	8A
		Lock-up disengaged	Approximately 1 A
26 L/U & Low & Rev. brake SOL. output	L/U & Low & Rev. brake SOL. output	Lock-up engaged (warmed up and constant speed driving)	0 A
		Lock-up disengaged	1-3A
27 2-6 brak monitor	2-6 brake solenoid	Gear range: 1st, 3rd - 5th	0 A
	monitor	Gear range: 2nd or 6th	Approximately 1 A
28 2-6 bra	2-6 brake solenoid output	Gear range: 1st, 3rd - 5th	0 A
		Gear range: 2nd or 6th	1 – 3 A
	Low clutch solenoid	Gear range: 5th, 6th	0 A
	monitor	Gear range: 1st - 4th	Approximately 1 A
30	Low clutch solenoid output	Gear range: 5th, 6th	0 A
		Gear range: 1st - 4th	1-3A
31 3-5 reverse clutch SOL monitor	3-5 reverse clutch SOL.	Transmission range: N	Approximately 1 A
	monitor	Transmission range: R	0 A
32 3-5 reverse clutch SOL. output		Transmission range: N	1 – 3 A
	output	Transmission range: R	0 A
	High clutch solenoid	Gear range: 1st - 3rd	Approximately 1 A
	monitor	Gear range: 4th - 6th	0 A
	High clutch solenoid	Gear range: 1st - 3rd	1-3A
	output	Gear range: 4th - 6th	0 A