

## Field campaign

<b>Topic</b>	Rear brake pad - Shim installation (SC 20/32)
<b>Market area</b>	United States E05 Bentley USA and rest America (6E05)
<b>Brand</b>	Bentley
<b>Transaction No.</b>	2061344/1
<b>Campaign number</b>	EB74
<b>Note</b>	
<b>Type</b>	
<b>US code</b>	

## Vehicle data

### Bentayga

#### Sales types

Type	MY	Brand	Designation	Engine code	Gearbox code	Final drive code
4V1*	2021	E		*	*	*

## Documents

Document name
<a href="#">master.xml</a>
<a href="#">sc2032vinlist.pdf</a>

## Notes

### ▪ Repair instructions

### Technical background

Fitment of shims to the rear brake pads, specific grease should also be applied to the shims

### Remedy

In high ambient temperatures in conjunction with low speed, low pressure brake vibration is dampened by the fitment of shims and grease

### Customer notification

Customers do not need to be informed directly of this campaign. Please ensure that all affected vehicles are checked and repaired during the PDI procedure

### Warranty accounting instructions

#### Time to install shim set

Warranty Type 790  
 Damage Service Number EB74  
 Damage Code 0066

#### Labour

Labour operation code 46 38 42 50  
 Time 20TU  
 Criteria ID 01

#### Time to remove and refit rear brake pads

Labour operation code 46 38 20 50  
 Time 50TU

#### Time to remove and refit rear wheels

Labour operation code 44 05 20 00  
 Time 10TU

### Genuine parts

Part number	Description	Quantity
36A 698 219	Shim set for rear brake pads	1 set (1 set includes x4 shims – 1 for each pad)
G 052 560 A2	Vary Bond grease	1 = 1 x 100 gram

▪ **IMPORTANT:** 1 tube of vary bond grease can be used on multiple vehicles (approximately x1 tube can be used on up to a maximum of 20 vehicles)

Do Not order more grease in the event you already have stock

### Parts supply

When applicable the required replacement parts should be ordered from Bentley Motors Limited Crewe or through your regional Bentley parts distribution centre

### Parts despatch control

The required replacement parts should be ordered from Bentley Motors Limited Crewe or through your regional Bentley parts distribution centre.

## Repair instructions

### ▪ Notes

### Technical background

Fitment of shims to the rear brake pads, specific grease should also be applied to the shims

## Check

If the vehicle is not already listed as repaired in the "Repair History" (Elsa Pro), check for the yellow paint completion mark (see Identification section), should neither be evident continue with the procedure detailed in the "Work" section of this procedure.

## Control

All applicable VIN's require the procedure to be conducted during the PDI procedure

## Genuine parts

Part number	Description	Quantity
36A 698 219	Shim set for rear brake pads	1 set (1 set includes x4 shims – 1 for each pad)
G 052 560 A2	Vary Bond grease	1 = 1 x 100 gram

IMPORTANT: 1 tube of vary bond grease can be used on multiple vehicles (approximately x1 tube can be used on up to a maximum of 20 vehicles)

Do Not order more grease in the event you already have stock

## Work

VERY IMPORTANT: The application of the grease MUST be exactly as shown/detailed, Ensuring the exact amount of grease is applied to the locations shown

*NOTE: Warranty payments for repeat repairs will not be considered if the grease is deemed to have not been applied correctly*

1. Remove the rear brake pads as per Repair manual Rep.Gr 46- Rear Brake Pads - To Remove and Fit and check the actual condition of the brake pads – NOTE: Make note of the position of the rear pads for installation purposes.

CAUTION: The performance of the car will be affected if the brake pads are installed in the incorrect position

2. Carefully clean the back plate of the pad using a suitable brake cleaner IMPORTANT: Take care not to damage the rubber on the bonded shim

3. Install one shim from the shim kit 36A 698 219 to each rear brake pad, ensuring that when fitted the new shim is seated flat against the brake pad bonded shim

4. Referring to Figure 1 - Apply 6 dots of grease (< 1.0g in total) to the inside face of the clip on shim



Figure 1

- Referring to Figure 2 – Using a suitable spatula spread the grease to an even layer condition



Figure 2

- Assemble the clip-on shim onto the pad - Squeeze together firmly to remove any excess grease which comes out from between the new shim and the brake pad bonded shim NOTE: Ensure the new shim is seated flat against the brake pad bonded shim
5. Referring to Figures 3 and 4 - Clean the pad abutments & the spring clips, then apply a small dot of grease to them



Figure 3



Figure 4

- Clean the pad abutment faces on the calliper carrier – scrape off any dirt and brake dust which has accumulated, then use a suitable brake cleaner
  - Wipe the face of the piston to remove any brake dust or dirt
  - Refit the rear brake pads as per Repair manual Rep. Gr 46 - Rear Brake Pads - To Remove and Fit, taking care not to dis-lodge the grease/shims before the pads are in position.
6. Road test the vehicle as part of the PDI road test procedure
- On return from road test, visually check for any excess grease which may have come out from between the two shims and remove with suitable cleaner
7. On completion place a yellow paint completion mark on the brake fluid reservoir – Refer to the Identification section

### Identification



SJAAM2ZV6MC033545  
SJAAM2ZV9MC033572  
SJAAM2ZV5MC033648  
SJAAM2ZV5MC033651  
SJAAM2ZV7MC033652  
SJAAM2ZV4MC033687  
SJAAM2ZV6MC033691  
SJAAM2ZV8MC033692  
SJAAM2ZV6MC033710  
SJAAM2ZV0MC033721  
SJAAM2ZV3MC033731  
SJAAM2ZV4MC033737  
SJAAM2ZV6MC033738  
SJAAM2ZV6MC033741  
SJAAM2ZV5MC033746  
SJAAM2ZV9MC033748  
SJAAM2ZV2MC033753  
SJAAM2ZVXMC033757  
SJAAM2ZVXMC033760  
SJAAM2ZV5MC033763  
SJAAM2ZV4MC033771  
SJAAM2ZVXMC033774  
SJAAM2ZV5MC033777  
SJAAM2ZV7MC033781  
SJAAM2ZV3MC033793  
SJAAM2ZV9MC033796  
SJAAM2ZV2MC033798  
SJAAM2ZV4MC033804  
SJAAM2ZV1MC033825  
SJAAM2ZV3MC033826  
SJAAM2ZV7MC033828  
SJAAM2ZV2MC033834  
SJAAM2ZV1MC033839  
SJAAM2ZV8MC033840

SJAAM2ZV1MC033842  
SJAAM2ZV3MC033843  
SJAAM2ZV0MC033847  
SJAAM2ZV2MC033848  
SJAAM2ZV0MC033850  
SJAAM2ZV4MC033852  
SJAAM2ZV8MC033854  
SJAAM2ZVXMC033855  
SJAAM2ZV1MC033856  
SJAAM2ZV3MC033857  
SJAAM2ZV3MC033860  
SJAAM2ZV5MC033875  
SJAAM2ZV7MC033876  
SJAAM2ZV0MC033878  
SJAAM2ZV2MC033879  
SJAAM2ZV0MC033881  
SJAAM2ZVXMC033886  
SJAAL14VXMC033889  
SJAAM2ZV5MC033892  
SJAAM2ZV9MC033894  
SJAAM2ZV2MC033896  
SJAAM2ZV4MC033897  
SJAAM2ZV6MC033898  
SJAAM2ZV8MC033899  
SJAAM2ZV4MC033902  
SJAAM2ZV8MC033904  
SJAAM2ZVXMC033905  
SJAAM2ZV3MC033907  
SJAAM2ZV5MC033908  
SJAAM2ZV7MC033909  
SJAAM2ZV3MC033910  
SJAAM2ZV5MC033911  
SJAAM2ZV0MC033914  
SJAAM2ZV6MC033917

SJAAM2ZV2MC033929  
SJAAM2ZV4MC033933  
SJAAM2ZV3MC033941  
SJAAM2ZV8MC033949  
SJAAM2ZV8MC033952  
SJAAM2ZV7MC033957  
SJAAM2ZV9MC033961  
SJAAM2ZV1MC033968  
SJAAM2ZV7MC033974  
SJAAM2ZV4MC033981  
SJAAM2ZV5MC033987  
SJAAM2ZV9MC033989  
SJAAM2ZV9MC033992  
SJAAM2ZV4MC033995  
SJAAM2ZV2MC034000  
SJAAM2ZV8MC034003  
SJAAM2ZV5MC034010  
SJAAM2ZV9MC034012  
SJAAM2ZV8MC034017  
SJAAM2ZV1MC034019  
SJAAM2ZVXMC034021  
SJAAM2ZV3MC034023  
SJAAM2ZV0MC034027  
SJAAM2ZV3MC034037  
SJAAM2ZV2MC034045  
SJAAM2ZV6MC034047  
SJAAM2ZV8MC034051  
SJAAM2ZV7MC034056  
SJAAM2ZV9MC034057  
SJAAM2ZV7MC034171  
SJAAM2ZVXMC034245  
SJAAM2ZV9MC034267