

2021

**Pre-Delivery Inspection
Technician Reference Document**




Table of Contents

Technician Reference Document

Technician Reference Document Overview

The Pre-Delivery Inspection Technician Reference Document is designed to be a resource used in hand with the Pre-Delivery Inspection Checklist (PDI). The PDI Checklist has been simplified to make the process more efficient, and in doing so, this document has been created to be used as a reference for checklist items that may have additional information. On the PDI Checklist, you find that certain items have been notated with an asterisk symbol (*), this lets you know that additional information can be found in this Technician Reference Document.

Below you will find a list of each model, with the page numbers to their left. After navigating to the desired page, you will notice each model page is formatted similarly to the PDI Checklists. After each section title is the original checklist item, followed by any additional information specific to that model.

Table of Contents

3-4	A4/S4/A4 allroad
5-6	A5/S5/RS 5
7-9	A6/S6/A6 allroad/RS 6 Avant
10-12	A7/A7 PHEV/S7/RS 7
13-14	A8 L/A8 PHEV/S8
15-16	e-tron
17-18	Q3
19-21	Q5/Q5 PHEV/Q5 Sportback/SQ5
22-23	Q7/SQ7
24-25	Q8/SQ8/RS Q8
26-27	R8 Coupe/Spyder
28-29	TT/TTS/TT RS

A4/S4/A4 allroad

Technician Reference Document

Vehicle Preparation

▶ Perform any open campaigns

Follow instructions listed in campaign documentation

▶ Perform diagnostic work

Connect vehicle diagnostic tester

- ▶ Select “Diagnosis” mode and start diagnosis
- ▶ Perform vehicle identification
- ▶ Untick “Working with Guided Fault Finding”
- ▶ Switch to “Special functions” tab and select following program:

Delivery Inspection total

- ▶ Start program by selecting “Carry out check”
- ▶ Continue to follow instructions on screen and complete the process
- ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
- ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
- ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically
- ▶ **Install front license plate carrier (if necessary)**
 - ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

▶ Check all key buttons and features

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

Lighting and Windshield

▶ Test front washers (and headlight washers if equipped). Correct aim if necessary

Headlights must be on to test functionality of the headlight washers

Trunk Inspection

▶ Install wheel bolt cover removal tool from PDI kit into trunk tool kit

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit

Trunk Inspection (continued)

▶ Set spare tire pressure

See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet

▶ Check battery clamps for proper torque

Refer to Elsa Pro for specification

Interior

▶ Check operation of window, lock, and seat controls

Check operation of all switches: Locks, windows, seat adjustment, heated seats (if equipped) and child safety features

▶ Inspect mirrors for proper operation

Inspect folding, adjustments, right side tilt in reverse, heating

▶ Check rear view mirror operation

Check self-dimming function/lighting

▶ Verify proper operation of climate control

Ensure proper heating and A/C cooling and open all panel vents for all zones

▶ Inspect operation of all power outlets

Inspect operation of front outlet, aux. outlet under armrest, and rear outlets

▶ Check panoramic sunroof and sunshade operation

Verify open/close/vent/deflector at edge and sunshade operation

Settings

▶ Set Time source setting to “GPS” and set Auto daylight savings time to “on.”

Change time zone appropriate to the dealer location

▶ Verify and set language

This can be changed in the Settings menu by going to Home > Settings > Language & Keyboard

▶ Verify and set measurement units

This can be changed in the Settings menu by going to Home > Settings > General > Measurement Units

▶ Verify Speech Dialog System is operating

Press the “Talk” button and verify several commands

▶ Set “Entertain. Fad.” in Parking aid to an audible level

Via “Home > Vehicle > Parking Aid”

▶ Set “Music volume while parking” to medium

Accessed via MMI rear view camera display, “Home > Vehicle > Parking Aid” (applies to vehicles with park assist or rear view camera)





A4/S4/A4 allroad

Technician Reference Document

Settings (continued)

- ▶ **Set dealership location in navigation (if equipped)**
Set dealership location for following back to dealership during road test
- ▶ **Turn off Manual Speed Warning (if equipped)**
This can be changed in the Driver Assistance settings by going to [Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = "off"](#)

Media / Radio / SAT

- ▶ **Verify HD Radio is turned "off"**
This can be found in the [Home > Radio > Gear icon \(top right corner\)](#)

On-Hoist Inspection

- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers and center caps can be found in the PDI kit
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known "sold" unit, set to appropriate Normal Load Condition. See separate "Audi Normal Load Condition Tire Pressure Table" posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in [Home > Vehicle > Settings & Service > Tire pressure monitoring](#)

Driving Performance

- ▶ **Verify engine Start-Stop System functionality**
Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner's manuals. Additional supply can be ordered via the Brand Store on AccessAudi
- ▶ **Verify engine performance and acceleration**
Listen for abnormal noise/vibrations
- ▶ **Test drive vehicle applying brakes several times**
Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/vibration/pulsation
- ▶ **Calibrate rear view mirror**
Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

- ▶ **Verify operation of parking system (if equipped)**
Verify operation of Audi parking system sensors with rear view camera (if equipped)
- ▶ **Verify all vehicle Head-up display functionality (if equipped)**
Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-up display (as equipped)

Post-Road Test Inspection

- ▶ **Check engine oil level**
Fill oil to the max level when the vehicle is at operating temperature

Audi connect® (USA ONLY) (if equipped)

- ▶ **Turn on the Wi-Fi® hotspot (if equipped)**
Ensure the wireless network is turned on ([Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings](#))
- ▶ **Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)**
Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to "AUDI_MMI_XXXX", where XXXX = the last four digits of the VIN are automatically preset in the system
- ▶ **Enable satellite map view for navigation (if equipped)**
Enable satellite map view in the [Home > Navigation > Gear Icon \(top right corner\) > Map Settings > Satellite map](#), and verify the satellite imagery appears in the navigation map screen

A5/S5/RS 5

Technician Reference Document

Vehicle Preparation

▶ **Perform any open campaigns**

Follow instructions listed in campaign documentation

▶ **Perform diagnostic work**

Connect vehicle diagnostic tester

- ▶ Select “Diagnosis” mode and start diagnosis
- ▶ Perform vehicle identification
- ▶ Untick “Working with Guided Fault Finding”
- ▶ Switch to “Special functions” tab and select following program:

Delivery Inspection total

- ▶ Start program by selecting “Carry out check”
- ▶ Continue to follow instructions on screen and complete the process
- ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
- ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
- ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically

▶ **Install front license plate carrier (if necessary)**

- ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

▶ **Check all key buttons and features**

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

Lighting and Windshield

▶ **Test windshield washers. Correct aim if necessary**

Headlights must be on to test functionality of the headlight washers

Trunk Inspection

▶ **Install wheel bolt cover removal tool from PDI kit into trunk tool kit**

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit

Trunk Inspection (continued)

▶ **Set spare tire pressure**

See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet

▶ **Check battery clamps for proper torque**

Refer to Elsa Pro for specification

Interior

▶ **Check operation of window, lock, and seat controls**

Check operation of all switches: Locks, windows, seat adjustment, heated seats (if equipped) and child safety features

▶ **Inspect mirrors for proper operation**

Inspect folding, adjustments, right side tilt in reverse, heating (if equipped)

▶ **Check rear view mirror operation**

Check self-dimming function/lighting (if equipped)

▶ **Verify proper operation of climate control**

Ensure proper heating and A/C cooling and open all panel vents

▶ **Inspect operation of all power outlets**

Inspect operation of front outlet, aux. outlet under armrest, and rear outlets

▶ **Check panoramic sunroof and sunshade operation**

Verify open/close/vent/deflector at edge and sunshade operation

Settings

▶ **Set Time source setting to “GPS” and set Auto daylight savings time to “on.”**

Change time zone appropriate to the dealer location

▶ **Verify and set language**

This can be changed in the Settings menu by going to Home > Settings > Language & Keyboard

▶ **Verify and set measurement units**

This can be changed in the Settings menu by going to Home > Settings > General > Measurement Units

▶ **Verify Speech Dialog System is operating**

Press the “Talk” button and verify several commands

▶ **Set “Entertain. Fad.” in Parking aid to an audible level**

Via “Home > Vehicle > Parking Aid”

▶ **Set “Music volume while parking” to medium**

Accessed via MMI rear view camera display, “Home > Vehicle > Parking Aid” (applies to vehicles with park assist or rear view camera)





A5/S5/RS 5

Technician Reference Document

Settings (continued)

- ▶ **Set dealership location in navigation (if equipped)**
Set dealership location for following back to dealership during road test
- ▶ **Turn off Manual Speed Warning (if equipped)**
This can be changed in the Driver Assistance settings by going to [Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = "off"](#)

Media / Radio / SAT

- ▶ **Verify HD Radio is turned "off"**
This can be found in the [Home > Radio > Gear icon \(top right corner\)](#)

On-Hoist Inspection

- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers and center caps can be found in the PDI kit
- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known "sold" unit, set to appropriate Normal Load Condition. See separate "Audi Normal Load Condition Tire Pressure Table" posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in [Home > Vehicle > Settings & Service > Tire pressure monitoring](#)

Driving Performance

- ▶ **Verify engine Start-Stop System functionality**
Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner's manuals. Additional supply can be ordered via the Brand Store on AccessAudi
- ▶ **Verify engine performance and acceleration**
Listen for abnormal noise/vibrations
- ▶ **Test drive vehicle applying brakes several times**
Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation
- ▶ **Calibrate rear view mirror**
Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

- ▶ **Verify operation of parking system (if equipped)**
Verify operation of Audi parking system sensors with rear view camera (if equipped)
- ▶ **Verify all vehicle Head-up display functionality (if equipped)**
Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-Up Display (as equipped)

Convertible Functionality (if equipped)

- ▶ Test operation of power folding top
Perform with engine running to conserve battery power

Post-Road Test Inspection

- ▶ **Check engine oil level**
Fill oil to the max level when the vehicle is at operating temperature

Audi connect® (USA ONLY) (if equipped)

- ▶ **Turn on the Wi-Fi® hotspot (if equipped)**
Ensure the wireless network is turned on ([Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings](#))
- ▶ **Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)**
Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to "AUDI_MMI_XXXX", where XXXX = the last four digits of the VIN are automatically preset in the system
- ▶ **Enable satellite map view for navigation (if equipped)**
Enable satellite map view in the [Home > Navigation > Gear Icon \(top right corner\) > Map Settings > Satellite map](#), and verify the satellite imagery appears in the navigation map screen

A6/S6/A6 allroad/RS 6 Avant

Technician Reference Document

Vehicle Preparation

- ▶ **Perform any open campaigns**
Follow instructions listed in campaign documentation
- ▶ **Perform diagnostic work**
Connect vehicle diagnostic tester
 - ▶ Select “Diagnosis” mode and start diagnosis
 - ▶ Perform vehicle identification
 - ▶ Untick “Working with Guided Fault Finding”
 - ▶ Switch to “Special functions” tab and select following program:
Delivery Inspection total
 - ▶ Start program by selecting “Carry out check”
 - ▶ Continue to follow instructions on screen and complete the process
 - ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
 - ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
 - ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically
- ▶ **Install front license plate carrier (if necessary)**
 - ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

- ▶ **Check all key buttons and features**
Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)
- ▶ **Check all doors for proper power closing (if equipped)**
For vehicles equipped with the power door closing feature, check all doors for proper closing

Lighting and Windshield

- ▶ **Test front washers (and headlight washers if equipped). Correct aim if necessary**
Headlights must be on to test functionality of the headlight washers

Trunk Inspection

- ▶ **Install wheel bolt cover removal tool from PDI kit into trunk tool kit**
Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit
- ▶ **Set spare tire pressure**
See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet
- ▶ **Check battery clamps for proper torque**
Refer to Elsa Pro for specification
- ▶ **Place one PR Number Label in the Warranty and Maintenance Book inside front cover and one on the Rear Panel Sill Frame under the luggage compartment floor, if not already there**
For vehicles produced prior to September 12, 2018

Labels are located in the trunk on top of spare tire

Rear Panel Sill Frame location: Top Arrow




A6/S6/A6 allroad/RS 6 Avant

Technician Reference Document

Trunk Inspection (continued)

Warranty and Maintenance inside cover placement



Interior

- ▶ **Check operation of window, lock, and seat controls**
Check operation of all switches: Locks, windows, seat adjustment, heated seats and child safety features
- ▶ **Inspect mirrors for proper operation**
Inspect folding, adjustments, right side tilt in reverse, heating (if equipped)
- ▶ **Check rear view mirror operation**
Check self-dimming function/lighting (if equipped)
- ▶ **Verify operation of heated/ventilated and massaging seats (if equipped)**
Check both front and rear. Massaging feature is in the front seats only (if equipped)
- ▶ **Verify proper operation of climate control***
Ensure proper heating and A/C cooling, open all panel vents for all zones
- ▶ **Inspect operation of all power outlets**
Inspect operation of front outlet, aux. outlet under armrest, and rear outlets
- ▶ **Check sunroof and sunshade operation**
Verify open/close/vent/deflector at edge and sunshade operation

Settings

- ▶ **Set Time source setting to “GPS” and set Auto daylight savings time to “on”**
Change time zone appropriate to the dealer location
- ▶ **Verify and set language**
This can be changed in the Settings menu by going to Home > Settings > Language & Keyboard
- ▶ **Verify and set measurement units**
This can be changed in the Settings menu by going to Home > Settings > General > Measurement Units
- ▶ **Set “Entertain. Fad.” in Parking aid to an audible level**
Via “Home > Vehicle > Parking Aid”
- ▶ **Set “Music volume while parking” to medium**
Accessed via MMI rear view camera display, “Home > Vehicle > Parking Aid” (applies to vehicles with park assist or rear view camera)
- ▶ **Set dealership location in navigation**
Set dealership location for following back to dealership during road test
- ▶ **Turn off Manual Speed Warning (if equipped)**
This can be changed in the Driver Assistance settings by going to Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = “off”

Media / Radio / SAT

- ▶ **Verify HD Radio is turned “off”**
This can be found in the Home > Radio > Gear icon (top right corner)

On-Hoist Inspection

- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers can be found in the PDI kit
- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in Home > Vehicle > Settings & Service > Tire pressure monitoring



A6/S6/A6 allroad/RS 6 Avant

Technician Reference Document

Driving Performance

► **Verify engine Start-Stop System functionality**

Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner's manuals. Additional supply can be ordered via the Brand Store on AccessAudi

► **Verify engine performance and acceleration**

Listen for abnormal noise/vibrations

► **Test drive vehicle applying brakes several times**

Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation

► **Calibrate rear view mirror**

Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

► **Verify operation of parking system**

Verify operation of Audi parking system sensors with rear view camera (if equipped)

► **Verify all vehicle Head-up Display functionality (if equipped)**

Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-Up Display (as equipped)

Post-Road Test Inspection

► **Check engine oil level**

Fill oil to the max level when the vehicle is at operating temperature

Audi connect® (USA ONLY)

► **Turn on the Wi-Fi® hotspot (if equipped)**

Ensure the wireless network is turned on (Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings)

► **Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)**

Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to "AUDI_MMI_XXXX", where XXXX = the last four digits of the VIN are automatically preset in the system

► **Enable satellite map view for navigation (if equipped)**

Enable satellite map view in the Home > Navigation > Gear Icon (top right corner) > Map Settings > Satellite map, and verify the satellite imagery appears in the navigation map screen



A7/A7 PHEV/S7/RS 7

Technician Reference Document

Vehicle Preparation

- ▶ **Perform any open campaigns**
Follow instructions listed in campaign documentation
- ▶ **Perform diagnostic work**
Connect vehicle diagnostic tester
 - ▶ Select “Diagnosis” mode and start diagnosis
 - ▶ Perform vehicle identification
 - ▶ Untick “Working with Guided Fault Finding”
 - ▶ Switch to “Special functions” tab and select following program:
Delivery Inspection total
 - ▶ Start program by selecting “Carry out check”
 - ▶ Continue to follow instructions on screen and complete the process
 - ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
 - ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
 - ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically
- ▶ **Install front license plate carrier (if necessary)**
 - ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

- ▶ **Check all key buttons and features**
Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)
- ▶ **Check all doors for proper power closing (if equipped)**
For vehicles equipped with the power door closing feature, check all doors for proper closing

Lighting and Windshield

- ▶ **Test front washers (and headlight washers if equipped). Correct aim if necessary**
Headlights must be on to test functionality of the headlight washers

Trunk Inspection

- ▶ **Install wheel bolt cover removal tool from PDI kit into trunk tool kit**
Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit
- ▶ **Set spare tire pressure**
See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet
- ▶ **Check battery clamps for proper torque**
Refer to Elsa Pro for specification
- ▶ **Place one PR Number Label in the Warranty and Maintenance Book inside front cover and one on the Rear Panel Sill Frame under the luggage compartment floor, if not already there**
For vehicles produced prior to September 12, 2018

Labels are located in the trunk on top of spare tire

Rear Panel Sill Frame location: Top Arrow




A7/A7 PHEV/S7/RS 7

Technician Reference Document

Trunk Inspection (continued)

Warranty and Maintenance inside cover placement



Interior

- ▶ **Check operation of window, lock, and seat controls**
Check operation of all switches: Locks, windows, seat adjustment, heated seats and child safety features
- ▶ **Inspect mirrors for proper operation**
Inspect folding, adjustments, right side tilt in reverse, heating (if equipped)
- ▶ **Check rear view mirror operation**
Check self-dimming function/lighting (if equipped)
- ▶ **Verify operation of heated/ventilated and massaging seats (if equipped)**
Check both front and rear. Massaging feature is in the front seats only (if equipped)
- ▶ **Verify proper operation of climate control***
Ensure proper heating and A/C cooling, open all panel vents for all zones
- ▶ **Inspect operation of all power outlets**
Inspect operation of front outlet, aux. outlet under armrest, and rear outlets
- ▶ **Check sunroof and sunshade operation**
Verify open/close/vent/deflector at edge and sunshade operation

Settings

- ▶ **Set Time source setting to “GPS” and set Auto daylight savings time to “on”**
Change time zone appropriate to the dealer location
- ▶ **Verify and set language**
This can be changed in the Settings menu by going to Home > Settings > Language & Keyboard
- ▶ **Verify and set measurement units**
This can be changed in the Settings menu by going to Home > Settings > General > Measurement Units
- ▶ **Verify Speech Dialog System is operating**
Press the “Talk” button and verify several commands
- ▶ **Set “Entertain. Fad.” in Parking aid to an audible level**
Via “Home > Vehicle > Parking Aid”
- ▶ **Set “Music volume while parking” to medium**
Accessed via MMI rear view camera display, “Home > Vehicle > Parking Aid” (applies to vehicles with park assist or rear view camera)
- ▶ **Set dealership location in navigation**
Set dealership location for following back to dealership during road test
- ▶ **Turn off Manual Speed Warning (if equipped)**
This can be changed in the Driver Assistance settings by going to Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = “off”

Media / Radio / SAT

- ▶ **Verify HD Radio is turned “off”**
This can be found in the Home > Radio > Gear icon (top right corner)

On-Hoist Inspection

- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers can be found in the PDI kit
- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in Home > Vehicle > Settings & Service > Tire pressure monitoring





A7/A7 PHEV/S7/RS 7

Technician Reference Document

Driving Performance

► Verify engine Start-Stop System functionality

Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner's manuals. Additional supply can be ordered via the Brand Store on AccessAudi

► Verify engine performance and acceleration

Listen for abnormal noise/vibrations

► Test drive vehicle applying brakes several times

Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation

► Calibrate rear view mirror

Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

► Verify operation of parking system

Verify operation of Audi parking system sensors with rear view camera (if equipped)

► Verify all vehicle Head-up display functionality (if equipped)

Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-Up Display (as equipped)

Post-Road Test Inspection

► Check engine oil level

Fill oil to the max level when the vehicle is at operating temperature

Audi connect® (USA ONLY) (if equipped)

► Turn on the Wi-Fi® hotspot (if equipped)

Ensure the wireless network is turned on (Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings)

► Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)

Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to "AUDI_MMI_XXXX", where XXXX = the last four digits of the VIN are automatically preset in the system

► Enable satellite map view for navigation (if equipped)

Enable satellite map view in the Home > Navigation > Gear Icon (top right corner) > Map Settings > Satellite map, and verify the satellite imagery appears in the navigation map screen



A8 L/A8 PHEV/S8

Technician Reference Document

Vehicle Preparation

► Perform any open campaigns

Follow instructions listed in campaign documentation

► Perform diagnostic work

Connect vehicle diagnostic tester

- Select “Diagnosis” mode and start diagnosis
- Perform vehicle identification
- Untick “Working with Guided Fault Finding”
- Switch to “Special functions” tab and select following program:

Delivery Inspection total

- Start program by selecting “Carry out check”
 - Continue to follow instructions on screen and complete the process
 - Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
 - The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
 - Exit diagnosis; diagnostic log for delivery inspection is sent automatically
- #### ► Install front license plate carrier (if necessary)
- Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

► Check all key buttons and features

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

► Check all doors for proper power closing

For vehicles equipped with the power door closing feature, check all doors for proper closing

Lighting and Windshield

► Test front washers (and headlight washers if equipped).

Correct aim if necessary

Headlights must be on to test functionality of the headlight washers

Trunk Inspection

► Install wheel bolt cover removal tool from PDI kit into trunk tool kit

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit

► Set spare tire pressure

See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet

► Check battery clamps for proper torque

Refer to Elsa Pro for specification

Interior

► Check operation of window, lock, and seat controls

Check operation of all switches: Locks, windows, seat adjustment, heated seats and child safety features

► Inspect mirrors for proper operation

Inspect folding, adjustments, right side tilt in reverse, heating (if equipped)

► Check rear view mirror operation

Check self-dimming function/lighting (if equipped)

► Verify operation of heated/ventilated and massaging seats (if equipped)

Check both front and rear. Massaging feature is in the front seats only (if equipped)

► Verify proper operation of climate control

Ensure proper heating and A/C cooling, open all panel vents for all zones

► Inspect operation of all power outlets

Inspect operation of front outlet, aux. outlet under armrest, and rear outlets

► Check panoramic sunroof and sunshade operation

Verify open/close/vent/deflector at edge and sunshade operation

Settings

► Set Time source setting to “GPS” and set Auto daylight savings time to “on”

Change time zone appropriate to the dealer location

► Verify and set language

This can be changed in the Settings menu by going to Home > Settings > Language & Keyboard

► Verify and set measurement units

This can be changed in the Settings menu by going to Home > Settings > General > Measurement Units

**A8 L/A8 PHEV/S8****Technician Reference Document****Settings (continued)**

- ▶ **Verify Speech Dialog System is operating**
Press the “Talk” button and verify several commands
- ▶ **Set “Entertain. Fad.” in Parking aid to an audible level**
Via “Home > Vehicle > Parking Aid”
- ▶ **Set “Music volume while parking” to medium**
Accessed via MMI rear view camera display, “Home > Vehicle > Parking Aid” (applies to vehicles with park assist or rear view camera)
- ▶ **Set dealership location in navigation (if equipped)**
Set dealership location for following back to dealership during road test
- ▶ **Turn off Manual Speed Warning (if equipped)**
This can be changed in the Driver Assistance settings by going to Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = “off”

Media / Radio / SAT

- ▶ **Verify HD Radio is turned “off”**
This can be found in the Home > Radio > Gear icon (top right corner)

On-Hoist Inspection

- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers can be found in the PDI kit
- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in Home > Vehicle > Settings & Service > Tire pressure monitoring

Driving Performance

- ▶ **Verify engine Start-Stop System functionality**
Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner’s manuals. Additional supply can be ordered via the Brand Store on AccessAudi
- ▶ **Verify engine performance and acceleration**
Listen for abnormal noise/vibrations

Driving Performance (continued)

- ▶ **Test drive vehicle applying brakes several times**
Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation
- ▶ **Calibrate rear view mirror**
Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

- ▶ **Verify operation of parking system**
Verify operation of Audi parking system sensors with rear view camera (if equipped)
- ▶ **Verify all vehicle Head-up display functionality (if equipped)**
Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-Up Display (as equipped)

Post-Road Test Inspection

- ▶ **Check engine oil level**
Fill oil to the max level when the vehicle is at operating temperature

Audi connect® (USA ONLY)

- ▶ **Turn on the Wi-Fi® hotspot (if equipped)**
Ensure the wireless network is turned on (Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings)
- ▶ **Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)**
Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to “AUDI_MMI_XXXX”, where XXXX = the last four digits of the VIN are automatically preset in the system
- ▶ **Enable satellite map view for navigation (if equipped)**
Enable satellite map view in the Home > Navigation > Gear Icon (top right corner) > Map Settings > Satellite map, and verify the satellite imagery appears in the navigation map screen



e-tron

Technician Reference Document

Vehicle Preparation

▶ **Perform any open campaigns**

Follow instructions listed in campaign documentation

▶ **Perform diagnostic work**

Connect vehicle diagnostic tester

- ▶ Select “Diagnosis” mode and start diagnosis
- ▶ Perform vehicle identification
- ▶ Untick “Working with Guided Fault Finding”
- ▶ Switch to “Special functions” tab and select following program:

Delivery Inspection total

- ▶ Start program by selecting “Carry out check”
 - ▶ Continue to follow instructions on screen and complete the process
 - ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
 - ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
 - ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically
- ▶ **Install front license plate carrier (if necessary)**
- ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

▶ **Check all key buttons and features**

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

▶ **Check all doors for proper power closing**

For vehicles equipped with the power door closing feature, check all doors for proper closing

Lighting and Windshield

▶ **Test front washers (and headlight washers if equipped). Correct aim if necessary**

Headlights must be on to test functionality of the headlight washers

Trunk Inspection

▶ **Install wheel bolt cover removal tool from PDI kit into trunk tool kit**

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit

Interior

▶ **Check operation of window, lock, and seat controls**

Check operation of all switches: Locks, windows, seat adjustment, heated seats and child safety features

▶ **Inspect mirrors for proper operation**

Inspect folding, adjustments, right side tilt in reverse, heating (if equipped)

▶ **Check rear view mirror operation**

Check self-dimming function/lighting (if equipped)

▶ **Verify operation of heated/ventilated and massaging seats (front/rear) (if equipped)**

Check both front and rear. Massaging feature is in the front seats only (if equipped)

▶ **Verify proper operation of climate control**

Ensure proper heating and A/C cooling, open all panel vents for all zones

▶ **Inspect operation of all power outlets**

Inspect operation of front outlet, aux. outlet under armrest, and rear outlets

▶ **Check panoramic sunroof and sunshade operation**

Verify open/close/vent/deflector at edge and sunshade operation

Settings

▶ **Set Time source setting to “GPS” and set Auto daylight savings time to “on”**

Change time zone appropriate to the dealer location

▶ **Verify and set language**

This can be changed in the Settings menu by going to Home > Settings > Language & Keyboard

▶ **Verify and set measurement units**

This can be changed in the Settings menu by going to Home > Settings > General > Measurement Units

▶ **Verify Speech Dialog System is operating**

Press the “Talk” button and verify several commands

▶ **Set “Entertain. Fad.” in Parking aid to an audible level**

Via “Home > Vehicle > Parking Aid”



**e-tron****Technician Reference Document****Settings (continued)**

- ▶ **Set “Music volume while parking” to medium**
Accessed via MMI rear view camera display, “[Home > Vehicle > Parking Aid](#)” (applies to vehicles with park assist or rear view camera)
- ▶ **Set dealership location in navigation (if equipped)**
Set dealership location for following back to dealership during road test
- ▶ **Turn off Manual Speed Warning (if equipped)**
This can be changed in the Driver Assistance settings by going to [Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = “off”](#)
- ▶ **Disable climate control via door unlock**
Main screen => Vehicle => Climate control => select small temperature gauge symbol in upper right section => settings (“wheel” upper right) => unselect (disable) “Start A/C after unlocking”. Check and adjust, if needed. Button position “off”, in left position

Media / Radio / SAT

- ▶ **Verify HD Radio is turned “off”**
This can be found in the [Home > Radio > Gear icon \(top right corner\)](#)

On-Hoist Inspection

- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers can be found in the PDI kit
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in [Home > Vehicle > Settings & Service > Tire pressure monitoring](#)

Driving Performance

- ▶ **Verify electric motor performance and acceleration**
Listen for abnormal noise/vibrations
- ▶ **Test drive vehicle applying brakes several times**
Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation

Driving Performance (continued)

- ▶ **Calibrate rear view mirror**
Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

- ▶ **Verify operation of parking system**
Verify operation of Audi parking system sensors with rear view camera (if equipped)
- ▶ **Verify all vehicle Head-up display functionality (if equipped)**
Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-Up Display (as equipped)

Audi connect® (USA ONLY) (if equipped)

- ▶ **Turn on the Wi-Fi® hotspot (if equipped)**
Ensure the wireless network is turned on ([Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings](#))
- ▶ **Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)**
Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to “[AUDI_MMI_XXXX](#)”, where XXXX = the last four digits of the VIN are automatically preset in the system
- ▶ **Enable satellite map view for navigation (if equipped)**
Enable satellite map view in the [Home > Navigation > Gear Icon \(top right corner\) > Map Settings > Satellite map](#), and verify the satellite imagery appears in the navigation map screen



Q3

Technician Reference Document

Vehicle Preparation

▶ **Perform any open campaigns**

Follow instructions listed in campaign documentation

▶ **Perform diagnostic work**

Connect vehicle diagnostic tester

- ▶ Select “Diagnosis” mode and start diagnosis
- ▶ Perform vehicle identification
- ▶ Untick “Working with Guided Fault Finding”
- ▶ Switch to “Special functions” tab and select following program:

Delivery Inspection total

- ▶ Start program by selecting “Carry out check”
- ▶ Continue to follow instructions on screen and complete the process
- ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
- ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
- ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically

▶ **Install front license plate carrier (if necessary)**

- ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

▶ **Check all key buttons and features**

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk manually and remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

Lighting and Windshield

▶ **Test front washers (and headlight washers if equipped). Correct aim if necessary**

Headlights must be on to test functionality of the headlight washers

Trunk Inspection

▶ **Verify power tailgate is operational and set default opening height**

Adjust the trunk lid opening height to 77.7 inches (197 cm) from the ground to the close button in the rear lid. Press and hold the close button in the rear lid for at least four seconds to program the opening height

▶ **Install wheel bolt cover removal tool from PDI kit into trunk lid tool kit**

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit to the right of the spare tire

▶ **Set spare tire pressure**

See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet

▶ **Check battery clamps for proper torque**

Refer to Elsa Pro for specification

Interior

▶ **Check operation of window, lock, and seat controls**

Check operation of all switches: Locks, windows, seat adjustment, heated seats (if equipped) and child safety features

▶ **Inspect mirrors for proper operation**

Inspect folding, adjustments, right side tilt in reverse, heating (if equipped)

▶ **Check rear view mirror operation**

Check self-dimming function/lighting (if equipped)

▶ **Verify proper operation of climate control**

Ensure proper heating and A/C cooling and open all panel vents

▶ **Inspect operation of all power outlets**

Inspect operation of front outlet, aux. outlet under armrest, and rear outlets

▶ **Check panoramic sunroof and sunshade operation**

Verify open/close/vent/deflector at edge and sunshade operation

Settings

▶ **Set Time source setting to “GPS” and set Auto daylight savings time to “on.” (if equipped with navigation)**

Change time zone appropriate to the dealer location



Q3

Technician Reference Document

Settings (continued)

- ▶ **Set “Entertain. Fad.” in Parking aid to an audible level (if equipped)**
Via “ Menu > Vehicle > Left Option > Drive Assistance > Parking Aid”
- ▶ **Verify and set language and measurement units**
This can be changed in the Setup/Settings menu
- ▶ **Verify Speech Dialog System is operating**
Press the “Talk” button and verify several commands
- ▶ **Set dealership location in navigation (if equipped)**
Set dealership location for following back to dealership during road test

Media / Radio / SAT

- ▶ **Verify HD Radio is turned “off”**
This can be found in the Radio/Settings Menu

Audi connect® (USA ONLY) (if equipped)

- ▶ **Turn on the Wi-Fi® hotspot (if equipped)**
Ensure the wireless network is turned on (Telephone > Right Option > Wi-Fi® options > Wi-Fi® “On”)
- ▶ **Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)**
Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to “AUDIXXXXX”, where XXXXX = the last five digits of VIN that are automatically preset in the system
- ▶ **Enable satellite map view for navigation (if equipped)**
Enable satellite map view in the Navigation > Gear Icon > Map Settings, and verify the satellite imagery appears in the navigation map screen

On-Hoist Inspection

- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers and center caps can be found in the PDI kit
- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in Car/System menu

Driving Performance

- ▶ **Verify engine Start-Stop System functionality**
Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner’s manuals. Additional supply can be ordered via the Brand Store on AccessAudi
- ▶ **Verify engine performance and acceleration**
Listen for abnormal noise/vibrations
- ▶ **Test drive vehicle applying brakes several times**
Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation
- ▶ **Calibrate rear view mirror**
Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

- ▶ **Verify operation of parking system plus with rear cross traffic assist (if equipped)**
Verify operation of Audi parking system sensors with rear view camera

Post-Road Test Inspection

- ▶ **Check engine oil level**
Fill oil to the max level when the vehicle is at operating temperature



Q5/Q5 PHEV/Q5 Sportback/SQ5

Technician Reference Document

Vehicle Preparation

▶ Perform any open campaigns

Follow instructions listed in campaign documentation

▶ Perform diagnostic work

Connect vehicle diagnostic tester

- ▶ Select “Diagnosis” mode and start diagnosis
- ▶ Perform vehicle identification
- ▶ Untick “Working with Guided Fault Finding”
- ▶ Switch to “Special functions” tab and select following program:

Delivery Inspection total

- ▶ Start program by selecting “Carry out check”
- ▶ Continue to follow instructions on screen and complete the process
- ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
- ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
- ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically

▶ Install front license plate carrier (if necessary)

- ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

▶ Check all key buttons and features

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk manually and remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

▶ Check all doors for proper power closing (if equipped)

For vehicles equipped with the power door closing feature, check all doors for proper closing

Exterior (continued)

▶ Prepare the base bars for customer delivery (install bars only upon customer request)

Install the rubber strips to the top of the base carrier bars (do not install the carrier bars on the vehicle unless customer has requested). Repackage the bars into the box if they are not being installed on the vehicle. Retrieve the paper with the torque wrench key code from the base carrier bar box. Insert the paper with the key code into the owner’s literature wallet. Record torque wrench key code in the VDF to ensure it’s documented in the event the paper with the code is misplaced

Lighting and Windshield

▶ Test front washers (and headlight washers if equipped). Correct aim if necessary

Headlights must be on to test functionality of the headlight washers

Trunk Inspection

▶ Verify power tailgate is operational and set default opening height

Adjust the trunk lid opening height to 77.7 inches (197 cm) from the ground to the close button in the rear lid. Press and hold the close button in the rear lid for at least four seconds to program the opening height

▶ Install wheel bolt cover removal tool from PDI kit into trunk lid toolkit

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit to the right of the spare tire

▶ Set spare tire pressure

See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet

▶ Check battery clamps for proper torque

Refer to Elsa Pro for specification

Interior

▶ Check operation of window, lock, and seat controls

Check operation of all switches: Locks, windows, seat adjustment, heated seats (if equipped) and child safety features

▶ Inspect mirrors for proper operation

Inspect folding, adjustments, right side tilt in reverse, heating (if equipped)

▶ Check rear view mirror operation

Check self-dimming function/lighting (if equipped)

Q5/Q5 PHEV/Q5 Sportback/SQ5

Technician Reference Document

Interior (continued)

- ▶ **Verify proper operation of climate control**
Ensure proper heating and A/C cooling and open all panel vents
- ▶ **Inspect operation of all power outlets**
Inspect operation of front outlet, aux. outlet under armrest, and rear outlets
- ▶ **Check panoramic sunroof and sunshade operation**
Verify open/close/vent/deflector at edge and sunshade operation

Settings

- ▶ **Set Time source setting to “GPS” and set Auto daylight savings time to “on.”**
Change time zone appropriate to the dealer location
- ▶ **Verify and set language**
This can be changed in the Settings menu by going to [Home > Settings > Language & Keyboard](#)
- ▶ **Verify and set measurement units**
This can be changed in the Settings menu by going to [Home > Settings > General > Measurement Units](#)
- ▶ **Verify Speech Dialog System is operating**
Press the “Talk” button and verify several commands
- ▶ **Set “Entertain. Fad.” in Parking aid to an audible level**
Via [“Home > Vehicle > Parking Aid”](#)
- ▶ **Set “Music volume while parking” to medium**
Accessed via MMI rear view camera display, [“Home > Vehicle > Parking Aid”](#) (applies to vehicles with park assist or rear view camera)
- ▶ **Set dealership location in navigation (if equipped)**
Set dealership location for following back to dealership during road test
- ▶ **Turn off Manual Speed Warning**
This can be changed in the Driver Assistance settings by going to [Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = “off”](#)

Media / Radio / SAT

- ▶ **Verify HD Radio is turned “off”**
This can be found in the [Home > Radio > Gear icon \(top right corner\)](#)

On-Hoist Inspection

- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers and center caps can be found in the PDI kit. When installing, ensure proper alignment to the valve stem (indentation in the wheel) lines up with the tab on the center cap to ensure correct mounting
- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in [Home > Vehicle > Settings & Service > Tire pressure monitoring](#)

Driving Performance

- ▶ **Verify engine Start-Stop System functionality**
Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner’s manuals. Additional supply can be ordered via the Brand Store on AccessAudi
- ▶ **Verify engine performance and acceleration**
Listen for abnormal noise/vibrations
- ▶ **Test drive vehicle applying brakes several times**
Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation
- ▶ **Calibrate rear view mirror**
Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

- ▶ **Verify operation of parking system**
Verify operation of Audi parking system sensors with rear view camera (if equipped)
- ▶ **Verify all vehicle Head-up display functionality (if equipped)**
Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-Up Display (as equipped)

Post-Road Test Inspection

- ▶ **Check engine oil level**
Fill oil to the max level when the vehicle is at operating temperature



Q5/Q5 PHEV/Q5 Sportback/SQ5 Technician Reference Document

Audi connect® (USA ONLY) (if equipped)

► Turn on the Wi-Fi® hotspot (if equipped)

Ensure the wireless network is turned on (Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings)

► Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)

Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to “AUDI_MMI_XXXX”, where XXXX = the last four digits of the VIN are automatically preset in the system

► Enable satellite map view for navigation (if equipped)

Enable satellite map view in the Home > Navigation > Gear Icon (top right corner) > Map Settings > Satellite map, and verify the satellite imagery appears in the navigation map screen



Q7/SQ7

Technician Reference Document

Vehicle Preparation

▶ **Perform any open campaigns**

Follow instructions listed in campaign documentation

▶ **Perform diagnostic work**

Connect vehicle diagnostic tester

- ▶ Select “Diagnosis” mode and start diagnosis
- ▶ Perform vehicle identification
- ▶ Untick “Working with Guided Fault Finding”
- ▶ Switch to “Special functions” tab and select following program:

Delivery Inspection total

- ▶ Start program by selecting “Carry out check”
 - ▶ Continue to follow instructions on screen and complete the process
 - ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
 - ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
 - ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically
- ▶ **Install front license plate carrier (if necessary)**
- ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

▶ **Check all key buttons and features**

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk manually and remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

▶ **Check all doors for proper power closing (if equipped)**

For vehicles equipped with the power door closing feature, check all doors for proper closing

Lighting and Windshield

▶ **Test front washers (and headlight washers if equipped). Correct aim if necessary**

Headlights must be on to test functionality of the headlight washers

Trunk Inspection

▶ **Verify power tailgate is operational and set to maximum opening height (if equipped)**

Press and hold the close button in the rear lid for at least four seconds to program the opening height. Verify operation of handsfree release (if equipped)

▶ **Install wheel bolt cover removal tool from PDI kit into trunk lid toolkit**

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit to the right of the spare tire

▶ **Check battery clamps for proper torque**

Refer to Elsa Pro for specification

Interior

▶ **Check operation of window, lock, and seat controls**

Check operation of all switches: Locks, windows, seat adjustment, heated seats (if equipped) and child safety features

▶ **Inspect mirrors for proper operation**

Inspect folding, adjustments, right side tilt in reverse, heating (if equipped) and child safety features

▶ **Check rear view mirror operation**

Check self-dimming function/lighting (if equipped)

▶ **Verify operation of heated/ventilated and massaging seats (if equipped)**

Check both front and rear. Massaging feature is in the front seats only (if equipped)

▶ **Verify operation of manual folding 2nd row and power folding 3rd row seats**

Controls for the power folding 3rd row are located in the trunk

▶ **Verify proper operation of climate control**

Ensure proper heating and A/C cooling and open all panel vents

▶ **Inspect operation of all power outlets**

Inspect operation of front outlet, aux. outlet under armrest, and rear outlets

▶ **Check panoramic sunroof and sunshade operation**

Verify open/close/vent/deflector at edge and sunshade operation

Settings

▶ **Set Time source setting to “GPS” and set Auto daylight savings time to “on.”**

Change time zone appropriate to the dealer location



Q7/SQ7

Technician Reference Document

Settings (continued)

- ▶ **Verify and set language**
This can be changed in the Settings menu by going to [Home > Settings > Language & Keyboard](#)
- ▶ **Verify and set measurement units**
This can be changed in the Settings menu by going to [Home > Settings > General > Measurement Units](#)
- ▶ **Verify Speech Dialog System is operating**
Press the “Talk” button and verify several commands
- ▶ **Set “Entertain. Fad.” in Parking aid to an audible level**
Via [“Home > Vehicle > Parking Aid”](#)
- ▶ **Set “Music volume while parking” to medium**
- ▶ Accessed via MMI rear view camera display, [“Home > Vehicle > Parking Aid”](#) (applies to vehicles with park assist or rear view camera)
- ▶ **Set dealership location in navigation (if equipped)**
Set dealership location for following back to dealership during road test
- ▶ **Turn off Manual Speed Warning (if equipped)**
This can be changed in the Driver Assistance settings by going to [Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = “off”](#)

Media / Radio / SAT

- ▶ **Verify HD Radio is turned “off”**
This can be found in the [Home > Radio > Gear icon \(top right corner\)](#)

On-Hoist Inspection

- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers and center caps can be found in the PDI kit
- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in [Home > Vehicle > Settings & Service > Tire pressure monitoring](#)

Driving Performance

- ▶ **Verify engine Start-Stop System functionality**
Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner’s manuals. Additional supply can be ordered via the Brand Store on AccessAudi
- ▶ **Verify engine performance and acceleration**
Listen for abnormal noise/vibrations
- ▶ **Test drive vehicle applying brakes several times**
Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation
- ▶ **Calibrate rear view mirror**
Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance

- ▶ **Verify operation of parking system**
Verify operation of Audi parking system sensors with rear view camera (if equipped)
- ▶ **Verify all vehicle Head-up display functionality (if equipped)**
Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-Up Display (as equipped)

Post-Road Test Inspection

- ▶ **Check engine oil level**
Fill oil to the max level when the vehicle is at operating temperature

Audi connect® (USA ONLY) (if equipped)

- ▶ **Turn on the Wi-Fi® hotspot (if equipped)**
Ensure the wireless network is turned on ([Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings](#))
- ▶ **Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)**
Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to [“AUDI_MMI_XXXX”](#), where [XXXX = the last four digits of the VIN are automatically preset in the system](#)
- ▶ **Enable satellite map view for navigation (if equipped)**
Enable satellite map view in the [Home > Navigation > Gear Icon \(top right corner\) > Map Settings > Satellite map](#), and verify the satellite imagery appears in the navigation map screen



Q8/SQ8/RS Q8

Technician Reference Document

Vehicle Preparation

▶ Perform any open campaigns

Follow instructions listed in campaign documentation

▶ Perform diagnostic work

Connect vehicle diagnostic tester

- ▶ Select “Diagnosis” mode and start diagnosis
- ▶ Perform vehicle identification
- ▶ Untick “Working with Guided Fault Finding”
- ▶ Switch to “Special functions” tab and select following program:

Delivery Inspection total

- ▶ Start program by selecting “Carry out check”
- ▶ Continue to follow instructions on screen and complete the process
- ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
- ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
- ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically
- ▶ **Install front license plate carrier (if necessary)**
 - ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

▶ Check all key buttons and features

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk manually and remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

▶ Check all doors for proper power closing (if equipped)

For vehicles equipped with the power door closing feature, check all doors for proper closing

Lighting and Windshield

▶ Test front washers (and headlight washers if equipped). Correct aim if necessary

Headlights must be on to test functionality of the headlight washers

Trunk Inspection

▶ Verify power tailgate is operational and set to maximum opening height (if equipped)

Press and hold the close button in the rear lid for at least four seconds to program the opening height. Verify operation of handsfree release (if equipped)

▶ Install wheel bolt cover removal tool from PDI kit into trunk lid toolkit

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit to the right of the spare tire

▶ Check battery clamps for proper torque

Refer to Elsa Pro for specification

▶ Set spare tire pressure

See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet

Interior

▶ Check operation of window, lock, and seat controls

Check operation of all switches: Locks, windows, seat adjustment, heated seats (if equipped) and child safety features

▶ Inspect mirrors for proper operation

Inspect folding, adjustments, right side tilt in reverse, heating (if equipped) and child safety features

▶ Check rear view mirror operation

Check self-dimming function/lighting (if equipped)

▶ Verify operation of heated/ventilated and massaging seats (if equipped)

Check both front and rear. Massaging feature is in the front seats only (if equipped)

▶ Verify proper operation of climate control

Ensure proper heating and A/C cooling and open all panel vents

▶ Inspect operation of all power outlets

Inspect operation of front outlet, aux. outlet under armrest, and rear outlets

▶ Check panoramic sunroof and sunshade operation

Verify open/close/vent/deflector at edge and sunshade operation

Settings

▶ Set Time source setting to “GPS” and set Auto daylight savings time to “on.”

Change time zone appropriate to the dealer location

**Q8/SQ8/RS Q8****Technician Reference Document****Settings (continued)****► Verify and set language**

This can be changed in the Settings menu by going to [Home > Settings > Language & Keyboard](#)

► Verify and set measurement units

This can be changed in the Settings menu by going to [Home > Settings > General > Measurement Units](#)

► Verify Speech Dialog System is operating

Press the “Talk” button and verify several commands

► Set “Entertain. Fad.” in Parking aid to an audible level

Via [“Home > Vehicle > Parking Aid”](#)

► Set “Music volume while parking” to medium

Accessed via MMI rear view camera display, [“Home > Vehicle > Parking Aid”](#) (applies to vehicles with park assist or rear view camera)

► Set dealership location in navigation

Set dealership location for following back to dealership during road test

► Turn off Manual Speed Warning (if equipped)

This can be changed in the Driver Assistance settings by going to [Home > Vehicle > Driver Assistance > Speed Warning > Manual Warning Threshold = “off”](#)

Media / Radio / SAT**► Verify HD Radio is turned “off”**

This can be found in the [Home > Radio > Gear icon \(top right corner\)](#)

On-Hoist Inspection**► Install wheel bolt covers and center caps as supplied**

Wheel bolt covers and center caps can be found in the PDI kit

► Inspect wheel bolts for proper torque

Use torque wrench to verify

► Set and store tire pressures for either sold vehicle OR stock inventory vehicle

If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in [Home > Vehicle > Settings & Service > Tire pressure monitoring](#)

Driving Performance**► Verify engine Start-Stop System functionality**

Verify the velum sticker is on the start/stop button. Remove the start/stop information card from the car kit and place it in the glove box with the owner’s manuals. Additional supply can be ordered via the Brand Store on AccessAudi

► Verify engine performance and acceleration

Listen for abnormal noise/vibrations

► Test drive vehicle applying brakes several times

Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/ vibration/pulsation

► Calibrate rear view mirror

Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting (if equipped)

Driver Assistance**► Verify operation of parking system**

Verify operation of Audi parking system sensors with rear view camera (if equipped)

► Verify all vehicle Head-up display functionality (if equipped)

Verify the image can be adjusted properly in the viewing area of the windshield. Verify NAV directions, speed, cruise control, and lane assist are all visible in Head-Up Display (as equipped)

Post-Road Test Inspection**► Check engine oil level**

Fill oil to the max level when the vehicle is at operating temperature

Audi connect® (USA ONLY) (if equipped)**► Turn on the Wi-Fi® hotspot (if equipped)**

Ensure the wireless network is turned on ([Home > Settings > Connection Settings > Wi-Fi > Wi-Fi hotspot settings](#))

► Check Wi-Fi® hotspot visibility. No data available at PDI (if equipped)

Check Wi-Fi® hotspot functionality is enabled and verify the SSID is set to [“AUDI_MMI_XXXX”](#), where XXXX = the last four digits of the VIN are automatically preset in the system

► Enable satellite map view for navigation (if equipped)

Enable satellite map view in the [Home > Navigation > Gear Icon \(top right corner\) > Map Settings > Satellite map](#), and verify the satellite imagery appears in the navigation map screen

R8 Coupe & Spyder

Technician Reference Document

Vehicle Preparation

► **Set adaption channel to enable CD Ripping using Guided Functions**

Set adaptation channel (via Special functions > Service work > 5F-Activating/deactivating storage of music). Also referred to as CD Ripping. Perform 3 button reset of the MMI to complete the activation. Refer to the owner’s manual for model-specific button sequence

► **Perform any open campaigns**

Follow instructions listed in campaign documentation

► **Perform diagnostic work**

Connect vehicle diagnostic tester

- Select “Diagnosis” mode and start diagnosis
- Perform vehicle identification
- Untick “Working with Guided Fault Finding”
- Switch to “Special functions” tab and select following program:

Delivery Inspection total

- Start program by selecting “Carry out check”
- Continue to follow instructions on screen and complete the process
- Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
- The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
- Exit diagnosis; diagnostic log for delivery inspection is sent automatically

Exterior

► **Check all key buttons and features**

Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk remotely lock/unlock with all keys, including all door handle sensors with Advanced Key

Lighting and Windshield

► **Test front washers. Correct aim if necessary**

Headlights must be on to test functionality of the headlight washers

Luggage Compartment

► **Install wheel bolt cover removal tool from PDI kit into trunk tool kit**

Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit

► **Check battery clamps for proper torque**

Refer to Elsa Pro for specification

Interior

► **Check operation of window, lock, and seat controls**

Check operation of all switches: Locks, windows, seat adjustment, heated seats (if equipped) and child safety features

► **Inspect mirrors for proper operation**

Inspect folding, adjustments, right side tilt in reverse, heating

► **Check rear view mirror operation**

Check self-dimming function/lighting

► **Verify proper operation of climate control**

Ensure proper heating and A/C cooling and open all panel vents for all zones

► **Inspect operation of all power outlets**

Inspect operation of front outlet, aux. outlet under armrest

Settings

► **Set Time source setting to “GPS” and set Auto daylight savings time to “on.”**

Change time zone appropriate to the dealer location

► **Verify and set language and measurement units**

This can be changed in the Settings menu by going to Menu > Vehicle > Vehicle settings

► **Verify Speech Dialog System is operating**

Press the “Talk” button and verify several commands

► **Set “Entertain. Fad.” in Parking aid to an audible level**

Via “Menu > Vehicle > Left Option > Driver Assistance > Parking Aid”

► **Set dealership location in navigation**

Set dealership location for following back to dealership during road test

► **Turn off Manual Speed Warning**

This can be changed in the Driver Assistance settings by going to Menu > Vehicle > Driver Assistance > Speed Warning > Manual->Select Off



R8 Coupe & Spyder

Technician Reference Document

Media / Radio / SAT

- ▶ **Verify HD Radio is turned “off”**
This can be found in the Radio/Settings Menu

Audi connect® (USA ONLY)

- ▶ **Turn on the Wi-Fi® hotspot**
Ensure the wireless network is turned on (Telephone > Options > Wi-Fi® options > Wi-Fi® Mode “Hotspot”)
- ▶ **Check Wi-Fi® hotspot visibility. No data available at PDI due to dealer demo mode**
Check Wi-Fi® hotspot functionality is enabled and verify the Access point (SSID) is set to “Audi_MMI_XXXX”, where XXXX is the last four digits of the VIN. Via Telephone > Options > Wi-Fi® options > Wi-Fi® Mode “Hotspot” > Hotspot settings > Access point (SSID)
- ▶ **Enable satellite map view for navigation**
Enable satellite map view in the Navigation > Gear icon > Map Settings, and verify the satellite imagery appears in the navigation map screen

On-Hoist Inspection

- ▶ **Inspect wheel bolts for proper torque**
Use torque wrench to verify
- ▶ **Install wheel bolt covers and center caps as supplied**
Wheel bolt covers and center caps can be found in the PDI kit
- ▶ **Set and store tire pressures for either sold vehicle OR stock inventory vehicle**
If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in Car/System menu

Driving Performance

- ▶ **Verify engine performance and acceleration**
Listen for abnormal noise/vibrations
- ▶ **Test drive vehicle applying brakes several times**
Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/vibration/pulsation
- ▶ **Calibrate rear view mirror**
Calibrate rear view mirror compass to proper zone and check self-dimming function/lighting

Driver Assistance

- ▶ **Verify operation of Audi parking system plus**
Verify operation of Audi parking system sensors with rear view camera

Convertible Functionality (if equipped)

- ▶ **Test operation of power folding top**
Perform with engine running to conserve battery power

Post-Road Test Inspection

- ▶ **Check engine oil level**
Fill oil to the max level when the vehicle is at operating temperature



TT Coupe & Roadster/TTS/TT RS

Technician Reference Document

Vehicle Preparation

- ▶ **Set adaption channel to enable CD Ripping using Guided Functions (if equipped with NAV)**
Set adaptation channel (via Special functions > Service work > 5F-Activating/deactivating storage of music). Also referred to as CD Ripping. Perform 3 button reset of the MMI to complete the activation. Refer to the owner’s manual for model-specific button sequence
- ▶ **Perform any open campaigns**
Follow instructions listed in campaign documentation
- ▶ **Perform diagnostic work**
Connect vehicle diagnostic tester
 - ▶ Select “Diagnosis” mode and start diagnosis
 - ▶ Perform vehicle identification
 - ▶ Untick “Working with Guided Fault Finding”
 - ▶ Switch to “Special functions” tab and select following program:
Delivery Inspection total
 - ▶ Start program by selecting “Carry out check”
 - ▶ Continue to follow instructions on screen and complete the process
 - ▶ Switch to the “Control units” tab, press the “Guided Fault Finding” button and launch Guided Fault Finding as far as the test plan
 - ▶ The static event memory entries must be evaluated and, if necessary, processed using Guided Fault Finding
 - ▶ Exit diagnosis; diagnostic log for delivery inspection is sent automatically
- ▶ **Install front license plate carrier (if necessary)**
 - ▶ Retain any removed trim required for carrier installation and give to the customer. If no front license plate carrier is necessary ensure the carrier remains in the trunk for the customer

Exterior

- ▶ **Check all key buttons and features**
Check functionality of all keys. Verify vehicle starts and runs with all keys and the start/stop button. Verify all doors and trunk remotely lock/unlock with all keys, including all door handle sensors with Advanced Key (if equipped)

Lighting and Windshield

- ▶ **Test front washers. Correct aim if necessary**
Headlights must be on to test functionality of the headlight washers

Trunk Inspection

- ▶ **Install wheel bolt cover removal tool from PDI kit into trunk tool kit**
Install wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) into trunk tool kit
- ▶ **Set spare tire pressure (NA for TT RS)**
See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet under Pre-Delivery Inspection
- ▶ **Check battery clamps for proper torque**
Refer to Elsa Pro for specification

Interior

- ▶ **Check operation of window, lock, and seat controls**
Check operation of all switches: Locks, windows, seat adjustment, heated seats (if equipped) and child safety features
- ▶ **Inspect mirrors for proper operation**
Inspect folding, adjustments, right side tilt in reverse, heating
- ▶ **Check rear view mirror operation**
Check self-dimming function/lighting (if equipped)
- ▶ **Verify proper operation of climate control**
Ensure proper heating and A/C cooling and open all panel vents for all zones
- ▶ **Inspect operation of all power outlets**
Inspect operation of front outlet, aux. outlet under armrest, and rear outlets

Settings

- ▶ **Set Time source setting to “GPS” and set Auto daylight savings time to “on.”**
Change time zone appropriate to the dealer location
- ▶ **Verify and set language and measurement units**
This can be changed in the Settings menu by going to Menu > Vehicle > Vehicle settings
- ▶ **Verify Speech Dialog System is operating**
Press the “Talk” button and verify several commands
- ▶ **Set “Entertain. Fad.” in Parking aid to an audible level**
Via “Menu > Vehicle > Left Option > Driver Assistance > Parking Aid”
- ▶ **Set dealership location in navigation (if equipped)**
Set dealership location for following back to dealership during road test





TT Coupe & Roadster/TTS/TT RS Technician Reference Document

Settings (continued)

► Turn off Manual Speed Warning (if equipped)

This can be changed in the Driver Assistance settings by going to Menu > Vehicle > Driver Assistance > Speed Warning > Manual->Select Off

Media / Radio / SAT

► Verify HD Radio is turned “off”

This can be found in the Radio/Settings Menu

On-Hoist Inspection

► Inspect wheel bolts for proper torque

Use torque wrench to verify

► Install wheel bolt covers and center caps as supplied

Wheel bolt covers and center caps can be found in the PDI kit

► Set and store tire pressures for either sold vehicle OR stock inventory vehicle

If a known “sold” unit, set to appropriate Normal Load Condition. See separate “Audi Normal Load Condition Tire Pressure Table” posted on ServiceNet. If going to stock, set to maximum recommended tire pressures listed on the B-pillar door jamb, and store tire pressure values in Car/System menu

Driving Performance

► Verify engine performance and acceleration

Listen for abnormal noise/vibrations

► Test drive vehicle applying brakes several times

Apply brakes at least 4 times at 20 mph (35 km/h) to clean brake rotors. Check for abnormal noise/vibration/pulsation

Driver Assistance

► Verify operation of Audi parking system plus (if equipped)

Verify operation of Audi parking system sensors with rear view camera (if equipped)

Roadster Functionality (if equipped)

► Test operation of power folding top

Perform with engine running to conserve battery power

Post-Road Test Inspection

► Check engine oil level

Fill oil to the max level when the vehicle is at operating temperature

