

# World Standard Automatic Transmission Fluid

Service  
Category Drivetrain

Section Automatic Transmission/Transaxle

Market USA

Lexus Supports  
ASE Certification 

## Applicability

YEAR(S)	MODEL(S)	ADDITIONAL INFORMATION
2011 – 2015	CT200H	
2007 – 2015	ES350, GS350, GS450H, LS460, RX350	
2006	GS300	
2006 – 2007	GS430	
2008 – 2015	GS460, IS F, LS600H, LX570	
2010 – 2015	GX460, HS250H, IS250C, IS350C, RX450H	
2004 – 2009	GX470	
2006 – 2015	IS250, IS350, SC430	
2004 – 2006	LS430	
2004 – 2007	LX470	
2015	NX200T, RC F, RC350	
2006 – 2008	RX400H	

### REVISION NOTICE

October 7, 2014 Rev2:

- Applicability has been updated to include 2012 – 2015 model year applicable vehicles.

March 11, 2011 Rev1:

- Applicability has been updated to include 2007 – 2009 model year RX 350 vehicles.

Any previous printed versions of this service bulletin should be discarded.

## World Standard Automatic Transmission Fluid

---

### Important Information

- 100,000 Mile Maintenance Interval — Inspection only; ATF-WS does NOT require any flushing or changing during the life of the vehicle.
- The use of Genuine Toyota ATF-WS is recommended.
  - The use of additives or aftermarket fluids that are considered compatible or substitutes may result in shift concerns and damage to the internal transmission components.
  - ATF-WS is NOT compatible with T-IV or Dexron ATF.
- Containers storing Toyota ATF-WS should ALWAYS be sealed — If exposed to the atmosphere, ATF-WS may absorb moisture and potentially cause shift concerns if used in operation.
- One time use only.
  - When performing repairs on ATF-WS equipped transaxles, it is important to use only new, clean ATF-WS when refilling the ATM.
  - ATF-WS equipped ATMs may use the overflow type procedure — Any fluid drained from the overflow plug should be discarded following proper local regulations and never reused. Failure to do so could result in shift concerns and damage to the internal transmission components.