



(Back Office Only) Volvo Chassis - Enable Parking Brake Alarm, Parameters - US17 And Newer (INT-GEN2)



Internal Content

DEALER ID: A241298
 CREATED BY: A241298
 CREATED: Nov 20, 2017, 05:27PM
 LAST CHANGED BY: A241298
 LAST CHANGED: May 15, 2019, 07:28PM

To enable the Volvo chassis parking brake alarm function, the instrument cluster (IC) parameters should be set as shown below:

Sales Code For Park Brake Alarm: 3MBA1X

Please adjust the below variants accordingly.

RUJ
Sets the speaker configuration for Park Brake Alert
0 = Off
1 = Internal Speaker
2 = City Horn
3 = Both Internal Speaker and City Horn
LYL
Mute radio when park brake alert sounds.
0 = No
1 = Yes
SAC
Enables the 'Set the Parking Brake' Popup (PP) in Instrument Cluster / Driver Information Display

Variant	Variant Description	FamilyID	VariantID
ibol			

Live UI

PARKAL	park brake alarm, sounds if brake off & driver's door opened	3MB	A1X
UPARKAL	without park brake alarm	3MB	Z1X
3MB-B1X	park brake alarm, sounds if park brake applied & engine on	3MB	B1X
PARKAL2	park brake alarm, sound if brake & ignition off & ds door open	3MB	A2X
3MB-C1X	pbr alarm,el horn sound if pbr off,ds door opened,key on/off	3MB	C1X
PARKAL3	park brk alm, sound if brake off,eng. on, driver seat empty	3MB	A3X
3MB-D1X	pbr alarm,el horn sound if pbr off & drvr seat unoccupied	3MB	D1X

 Tags
[k28347011](#)[cu15](#)[cu12 cng](#)[cu9 cng](#)[cu9](#)[volvo](#)

Related links and attachments



Live UI

no links or attachments available



Feedback

[Give feedback](#)

to help improve the content of this article