Title:	Impel/Velocity™ Step Replacement			WE'VE GOT
Number:	PB_560	Release Date:	02/11/2022	YOUR BACK
Revision Number:	1	Revision Date:	11/23/2022	PRODUCT
Chassis Type:	Impel/Velocity™ SUPPORT			
Component Description:	Cab step options for discontinued step module Reference PSB0645 Impel/Velocity Power Steps			Pierce
Warranty:	N/A			
Parts:	See below			
Tools:	Typical shop tools			

# Subject:

Replacement step options for discontinued power steps on Impel/Velocity™ chassis.

# Purpose:

Required electrical component used to control the electrical steps has been discontinued by the manufacturer. The electric power step replacement/repair options available are as follows:

Option 1: Replace, rewire and weatherproof discontinued module (p/n 63-4750-0001)

This option is available if the module is the only part to be replaced.

The following parts are no longer available:

0	Part Number	o Item Description			
0	1768395	o STEP,UPPER			
0	1768402	o STEP,LOWER			
0	1768406	o CROSS LINK,LOWER			
0	1768408	o LINK,LONG			
0	1768409	o LINK,SHORT			
0	1800056	o CROSS LINK,UPPER			
0	1800057	o BRKT,UPPER ACTUATOR MOUNT			
0	1801040	o BRKT,SPRING PLUNGER MOUNT,LH			
0	1801041	o BRKT,SPRING PLUNGER MOUNT,RH			
0	1776622*	o ACTUATOR,ELECTRIC,POWER STEP			
*Limi	*Limited availability. Once current stocks are exhausted as of the time of this				
bulletin, then it will no longer be available.					

If any of these need to be replaced, then option 1 is not available.

Option 2: Replace with existing fixed option 0555486 Steps, 4-Door Cab, Dual, Imp/Vel

Option 3: Replace with new air steps option 0799676 Steps, 4-Door Cab, Automatic, Air, Imp/Vel

# **Description:**

Option 1: Replace, rewire and weatherproof module (p/n 63-4750-0001)

- ✓ Order parts:
  - o 4076068 MODULE, STEP ASSEMBLY 12AMP 8-18VDC
  - o 64-2343 RELAY, SPDT 30A 12VDC, ENCAPSUL W/RESISTOR W/TAB
  - o 64-2344 HARNESS, ENCAPSULATED RELAY
- ✓ Request wiring diagram 66-8000-354S
- ✓ Replacement module is not a direct replacement.

#### **PARTS BULLETIN #560**

- New unit is not waterproof and is intended for indoor use. Module must be mounted and wired in a weather-tight location. Unit is 4.125"L x 2.375"W x 1.00"H (H is to top of terminals).
- Operating temperature range is -40°C (-40°F) to +85°C (+185°F).
- o Module receives a positive signal rather than a negative, so wiring modifications will be required.

# Option 2: Replace with existing fixed option 0555486 Steps, 4-Door Cab, Dual, Imp/Vel

- ✓ Order one each of bill of material:
  - 1961803 0855-LOWER STEPS, FRT CAB
  - o 1961969 0855-LOWER STEPS, RR CAB
  - o 3542952 0855-CAB, DUAL STEP, LT (Standard step lighting)
- ✓ Request reference 3542952 REF,LOWER STEPS,DUAL

NOTE: If job is a two or three door cab, please submit an NPN request on Pierceparts.com



Option 2 Dual fixed steps

# Option 3: Replace power cab step system with new air step system option 0799676 Steps, 4-Door Cab, Automatic, Air, Imp/Vel

- ✓ Order one each of bill of materials:
  - o 3449946 0855-LOWER STEP
  - 3449019 0855-CAB STEP ELECTRICAL
  - 2993459 0855-AIR SYSTEM, LOWER STEP
- ✓ Request wiring diagram 66-8000-354B



Option 3 Automatic air step extended

# PARTS BULLETIN #560



Option 3 Automatic air steps retracted

If any additional support is needed, please open a technical support incident on Pierceparts.com.