

# Technical Service Bulletin



## 00 Oil draining - cleanliness

00 14 59 2029737/2 February 20, 2014. Supersedes Technical Service Bulletin Group 00 number 12-34 dated June 6, 2012 for reasons listed below.

Model(s)	Year	VIN Range	Vehicle-Specific Equipment
All	2008 - 2015	All	Not Applicable

## Condition

REVISION HISTORY		
Revision	Date	Purpose
2	-	Revised header data (Added model years) Revised overall bulletin for clarity
1	06/06/2012	Initial publication

The process of draining oil through the drain plug is not always tidy.

## Technical Background

When oil is drained through the drain plug, the oil might spill on components around the oil pan area. If it is not properly cleaned up, this spilled oil could drip after the procedure is complete, causing unnecessary customer complaints.

## Production Solution

Not applicable.

## Service

1. When necessary, use flexible oil funnel VAS 6675 (Figure 1) on difficult-to-reach places to prevent oil from spilling.
2. Clean any oil residue off of components before returning the vehicle to the customer.



**Note:**

For all non-electronic oil consumption tests, it is necessary to capture any spilled oil to ensure accuracy of the measurements.



**Note:**

See *Repair Manual >> Maintenance >> Maintenance Procedures >> Engine Oil, Draining/Extracting and Removing and Installing Filter >> 3.0 TFSI Gasoline Engine.*



**Figure 1.** Oil funnel VAS 6675.

## Warranty

This TSB is informational only and not applicable to any Audi warranty.

## Required Parts and Tools

Part Number	Part Description	Quantity
VAS 6675	Flexible oil funnel	1

## Additional Information

All parts and service references provided in this TSB (2029737) are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.