



## Flywheel Housing Thread Repair

Internal Content

Tye Saul

We have noticed an increase in flywheel housing replacements. It is possible when removing the flywheel housing some fasteners could break resulting in an unusable fastening point.



We recommend you attempt to repair before replacing the flywheel housing. Please use threaded inserts similar to the one below. Be certain to use the factory correct mounting hardware and compatible insert.

**NOTE: Do not use a HELI - COIL style insert.**



Each flywheel housing should have no more than 3 total repairs.

## Warranty

Claimable service time is available for bolt extractions.

 Tags

[flywheel housing bolt repair](#)

[flywheel housing](#)

[broken bolt](#)

 Live UI [ries](#) 

- Make and Model > Mack > CXU/CHU/PI - Pinnacle
- Make and Model > Mack > LEU - TerraPro Low Entry
- Make and Model > Mack > LR
- Make and Model > Mack > TD - Titan
- Make and Model > Volvo > VNL
- Make and Model > Volvo > VNR
- Make and Model > Volvo > VN (Previous)
- Make and Model > Volvo > VNM
- Make and Model > Volvo > VNX
- Make and Model > Volvo > VAH
- Make and Model > Volvo > VHD
- Make and Model > Mack > MRU/TE - TerraPro
- Vehicle System > Engine
- Vehicle System > Transmission
- Make and Model > Mack > AN - Anthem
- Make and Model > Mack > GU/GR - Granite

### Related links and attachments

No links or attachments available



### Feedback

[Give feedback](#)

to help improve the content of this article