

Manufacturer's Certificate

Freigabe/Approval 40/23 ENU 1701

Allocation of Approved Engine Oils MY 2024 (40/23)

Revision: This bulletin replaces bulletin Group 1 55/22, dated September 5, 2023.

Model Year: 2024

Vehicle Type: All Porsche series vehicles MY 2024

Validity: Worldwide

Oil Quality: **Only oils approved by Porsche from the current status of the corresponding approval lists** are to be used for the vehicle types mentioned.

Note: For model series up to and including MY 2020 (or for MY 2021, MY 2022, etc.), only the "Allocation of approved engine oils up to MY 2020 (or for MY 2021, MY 2022 etc.)" are to be used.

A **detailed list** of the approved oil types can be found under the respective "Overview of approved Porsche engine oils" in the PCSS.

From MY 2021, only OW-...oils may be used for all vehicles.

For classic vehicles, use only the list "Recommended engine oils for classic vehicles".

Porsche specification	C40	C40 GT	C30	C20			
Designation Unit							
Type 971, Panamera G2 II, MY 24							
Panamera	EA839 LK3dc						
Panamera 4		-	-	Х	-		
Panamera 4S / 4S E-Hybrid	EA839 LK3	-	-	Х	-		
Panamera 4 E-Hybrid	EA839 LK3dc	-	-	Х	-		
Panamera GTS	EA825 LK5dc	х	-	-	-		
Panamera Turbo S E-Hybrid EA825 LK5		Х	-	-	-		
Panamera Turbo S	EA825 LK5+	х	-	-	-		
Type 976, Panamera G3, MY 24							
Panamera	EA839 LK3dc	-	-	х	-		
Panamera 4							
Panamera 4S E-Hybrid EA839 LK3dc		-	-	Х	-		

Freigabe/Approval

1

1701 ENU 40/23

Manufacturer's Certificate

Porsche specification	C40	C40 GT	C30	C20		
Designation	Unit			-		
Panamera Turbo E-Hybrid	EA825 evo LK5dc	Х	-		-	
	Type 9YA, 9YB, Caye	nne E3, MY 2	24			
Cayenne	EA839 LK2	-	-	-	х	
Cayenne S	EA825 evo LK5	х	-	-	-	
Cayenne E-Hybrid	EA839 LK2	-	-	-	х	
Cayenne S E-Hybrid	EA839 LK2	-		-	х	
Cayenne GTS	EA825 evo LK5	х		-	-	
Cayenne Turbo E-Hybrid	EA825 evo LK5	х	-	-	-	
Cayenne Turbo GT	EA825 LK5+	х	-	-	-	
	Type 95B, Macar	III. MY 24				
Macan					x	
Macan T	EA888 evo4	-	-	-		
Macan S	EA839 LK3	-	-	Х	-	
Macan GTS	EA839 LK3	-		х	-	
	T 200 742					
740.0	Type 982, 718	5, MY24				
718 Boxster	EA9A2 2.01B4T	x	-	-		
718 Cayman						
718 Boxster S	EA9A2 2.5 I B4T	х	-	-	-	
718 Cayman S 718 Boxster GTS 4.0						
	EA9A2evo 4.01B6S	х		-	-	
718 Cayman GTS 4.0 718 GT4 RS						
EA9A1.5 4.01B6S		-	х	-	-	
718 Spyder RS		l				
	Type 992, Carre	ra, MY24				
Carrera						
Carrera 4	EA9A2evo 3.01B6T			-	-	
Carrera T						

Mar 25, 2024 Page 2 of 4

AfterSales

Manufacturer's Certificate

40/23 ENU 1701

Porsche specification	C40	C40 GT	C30	C20	
Designation	Unit			_	
Carrera S	EA9A2evo 3.01B6T	V			
Carrera 4S		Х	-	-	-
Carrera GTS	EA9A2evo 3.01B6T	V			
Carrera 4 GTS		Х	-	-	-
Turbo	EA9A2evo 3.8I B6T	v			
Turbo S		Х	-		-
GT3	EA9A1.5 4.01B6S				
GT3 RS		-	х	-	-
S/T					
Dakar	EA9A2evo 3.0I B6T	х	-	-	-

Legend

Information on Porsche specifications					
	C40	C40 GT	C30	C20	
Viscosity class	Multi-grade	Multi-grade	Multi-grade	Multi-grade	
	0W-40	0W-40	0W-30	0W-20	
Other definitions					
х	Approved				
-	Not used				

Viscosity:

The viscosity of an engine oil is specified by the SAE viscosity class.

The first number and the letter W (winter) identify the viscosity at low temperatures. This means that an oil with the specification "5W" is more viscous than oil with the specification "0W".

The second number indicates the viscosity at high temperatures. This means that an oil with the specification "40" is less viscous than oil with the specification "50".

Multi-grade oils are identified by both viscosity specifications, e.g. SAE 0W-40, 5W-40 or 5W-50.

Examples:

SAE 0W-40 and 5W-40 oils have the same viscosity at high temperatures, but at low temperatures, the "5W" oil is more viscous.

SAE 5W-40 and 5W-50 oils have the same viscosity at low temperatures, but at higher temperatures, the oil with viscosity class "40" is less viscous.

1 Frei	gab	e/Approval	Мари	ifacturor's Cortificato
1	01	enu 40/23	IVIAIIU	Manufacturer's Certificate

All engine oils approved by Porsche can be mixed provided they are of the same Porsche oil Miscibility: specification. This means that it is not necessary to flush the engine when the oil is changed if another type of oil is used. However, since every brand of oil has a specially adapted unique composition, the same brand and type of oil should be used for topping up between oil change intervals if possible.

Important Notice: Technical Bulletins issued by Porsche Cars North America, Inc. are intended only for use by professional automotive technicians who have attended Porsche service training courses. They are written to inform those technicians of conditions that may occur on some Porsche vehicles, or to provide information that could assist in the proper servicing of a vehicle. Porsche special tools may be necessary in order to perform certain operations identified in these bulletins. Use of tools and procedures other than those Porsche recommends in these bulletins may be detrimental to the safe operation of your vehicle, and may endanger the people working on it. Properly trained Porsche technicians have the equipment, tools, safety instructions, and know how to do the job properly and safely. Part numbers listed in these builtetins are for reference only. The work procedures updated electronically in the Porsche PIWIS diagnostic and testing device take precedence and, in the event of a discrepancy, the work procedures in the PIWIS Tester are the ones that must be followed.

© 2024 Porsche Cars North America, Inc.

Mar 25, 2024 Page 4 of 4

AfterSales