

2010-2014 Camry		2010-2014	FJ Cruiser	
2010-2014	Highlander	2010-2014	Prius	
2010-2014	Tundra	2010-2014	Sienna	
2010-2014	Matrix	2013-2014	Avalon HV	
2012-2014	Prius V	2010-2011, 2013- 2014	Land Cruiser	
2010-2014	4Runner	2010-2014	Sequoia	
2010-2014	Avalon	2010-2014	RAV4	
2010-2014	Venza	2010, 2012-2014	Prius PHV	
2010-2014	Yaris	2010-2014	Tacoma	
2010	Solara	2012-2014	Prius C	
2010-2014	Highlander HV	2010-2014	Camry HV	
2010-2014	Corolla			

CONDITION

Starting with the 2010 Model Year, Toyota began a gradual transition to the use of synthetic 0w-20 viscosity engine oil. There are multiple benefits of this oil, including:

- · Reduced friction and wear on engine surfaces
- Improved fuel economy
- Reduction in waste oil stream (in vehicles approved for 10,000 mile oil change intervals)
- Reduced maintenance cost (in vehicles approved for 10,000 mile oil change intervals)

Due to the improved performance and durability of 0w-20 synthetic oil, Toyota has extended the oil change intervals to 10,000 miles for most vehicles that require this oil. With this change, the following should be noted:

- The 2TR-FE (4Runner / Tacoma) and the 3UR-FBE (Flex Fuel Tundra / Sequoia) are the exceptions to this new change interval program; these engines have not been approved for the 10,000 mile interval at this time. A 5,000 mile oil change interval is still required for these vehicles. Also, the Flex Fuel 3UR-FBE requires a 2,500 mile interval when operated on E85 50% of the time or more.
- Only Toyota vehicles in which 0w-20 oil is <u>mandatory</u> (except for the 2TR-FE & 3UR-FBE Engines) have been approved for extended oil change intervals.
- Vehicles in which 0w-20 is an option to 5w-20 (or 5w-30) will continue to require 5,000 mile change intervals, even if 0w-20 oil is used.
- In the case of vehicles with 10,000 mile oil change intervals, the 5,000 mile <u>service</u> interval has not been eliminated. The traditional 5,000 mile maintenance procedures (such as tire rotation) will continue to be required, and the fluid levels (including engine oil) will need to be checked and adjusted at this time.
- If the vehicle operation meets the standard criteria for "Special Operating Conditions" such as: driving
 off-road, on dirt roads, towing a trailer, making repeated short trips under 32° F, or extensive idling; the
 engine oil must be replaced at 5,000 mile intervals, regardless of oil used.



Tech Tip T-TT-0262-13

February 04, 2014

Market

Oil Viscosity Applicability and Change Interval Guide USA

RECOMMENDATIONS

Please follow the charts on pages 2 & 3 to determine the proper oil viscosity, fill quantity, and proper <u>change</u> interval for 2010-2014 Model Year Toyota vehicles under non-severe usage.

	Vehicle	Engine	Model Year	Oil	Capacity w/ Filter Change	Change Interva
	4Runner	1GR-FE	2010-2014	0w-20	6.6	10,000 Miles
		2TR-FE	2010	0w-20	6.1	5,000 Miles
	FJ Cruiser	1GR-FE	2010-2014	0w-20	6.4	10,000 Miles
	Highlander -	1AR-FE	2010-2013	5w-20 or 0w-20	4.7	5,000 Miles
			2014	0W-20	4.6	10,000 Miles
		2GR-FE	2010	NOTE 1	6.4	5,000 Miles
			2011-2014	0w-20	6.4	10,000 Miles
	Highlander HV	3MZ-FE	2010	5w-20 or 0w-20	5.0	5,000 Miles
		2GR-FXE	2011-2014	0w-20	6.4	10,000 Miles
			2010	5w-20 or 0w-20	NOTE 2	5,000 Miles
	Land Cruiser	3UR-FE	2011		7.9	5,000 Miles
			2013-2014	0w-20	7.9	10,000 Miles
		2AR-FE	2010-2012	5w-20 or 0w-20	4.7	5,000 Miles
	RAV4	2GR-FE	2010-2012	5w-30	6.4	5,000 Miles
		2AR-FE	2013-2014	0w-20	4.6	10,000 Miles
TRUCK		1UR-FE	2010-2013	0w-20	7.9	10,000 Miles
Ĕ			2010-2011	5w-20 or 0w-20	7.9	5,000 Miles
<u>S</u>	Sequoia	3UR-FE	2012-2014	0w-20	7.9	10,000 Miles
		3UR-FBE	2010-2011	5w-20 or 0w-20	7.9	5,000 Miles / Note 3
			2012-2014	0w-20	7.9	
	Sienna	1AR-FE	2011-2013	0w-20	4.7	10,000 Miles
		2GR-FE	2010	5w-30	6.4	5,000 Miles
			2011-2014	0w-20	6.4	10,000 Miles
	Tacoma	1GR-FE	2010-2014	5w-30	NOTE 4	5,000 Miles
		2TR-FE	2010	5w-20 or 0w-20	6.1	5,000 Miles
			2011-2014	0w-20	6.1	5,000 Miles
	Tundra	1GR-FE	2010	5w-30	NOTE 5	5,000 Miles
			2011-2014	0w-20	6.4	10,000 Miles
		1UR-FE	2010-2014	0w-20	7.9	10,000 Miles
		3UR-FE	2010-2011	5w-20 or 0w-20	7.9	5,000 Miles
			2012-2014	0w-20	7.9	10,000 Miles
		3UR-FBE	2010-2011	5w-20 or 0w-20	7.9	5,000 Miles /
- 7			2012-2014	0w-20	7.9	Note 3

NOTE 1. With Towing Package - 5w-30 / Without Towing Package - 5w-20

NOTE 2. If dip stick color is BLUE, fill quantity is 7.4 quarts. If dip stick is GREEN, fill quantity is 7.9 quarts

NOTE 3. Flex fuel vehicles that have been operated with E85 50% of the time or more, must have engine oil changed every

Expires on 02/04/2015 Ver. 2.2 09/06/2013 T



Tech Tip T-TT-0262-13

February 04, 2014

Subject Oil Viscosity Applicability and Change Interval Guide USA Applicability

RECOMMENDATIONS

2,500 miles

NOTE 4. 4.8 quarts for 2WD (except Pre-Runner), 5.5 quarts for 4X4 and Pre-Runner

NOTE 5. Vehicles built through Oct 2009 receive 4.8 quarts and vehicles built from Nov 2009 receive 5.5 quarts

	Vehicle	Engine	Model Year	Oil	Capacity w/ Filter Change	Change Interval
-	Avalon	2GR-FE	2010-2012	5w-30	6.4	5,000 Miles
			2013-2014	0w-20	6.4	10,000 Miles
	Avalon HV	2AR-FXE	2013-2014	0W-20	4.6	10,000 Miles
	Camry	2AR-FE	2010-2014	0w-20	4.7	10,000 Miles
		2GR-FE	2010-2011	5w-30	6.4	5,000 Miles
			2012-2014	0w-20	6.4	10,000 Miles
	Camry HV	2AZ-FXE	2010-2011	5w-20 or 0w-20	4.5	5,000 Miles
		2AR-FXE	2012-2014	0w-20	4.5	10,000 Miles
	Corolla	2ZR-FE	2010	5w-20 or 0w-20	4.4	5,000 Miles
-			2011-2014	0w-20	4.4	10,000 Miles
CAR		2ZR-FAE	2014	0w-20	4.2	10,000 Miles
		2AZ-FE	2010	5w-20 or 0w-20	4.0	5,000 Miles
	Matrix	2ZR-FE	2010	5w-20 or 0w-20	4.4	5,000 Miles
			2011-2013	0w-20	4.4	10,000 Miles
		2AZ-FE	2010-2013	5w-20 or 0w-20	4.0	5,000 Miles
	Prius	2ZR-FXE	2010-2014	0w-20	4.4	10,000 Miles
	Prius C	1NZ-FXE	2012-2014	0w-20	3.9	10,000 Miles
	Prius PHV	2ZR-FXE	2012-2014	0w-20	4.4	10,000 Miles
	Prius V	2ZR-FXE	2012-2014	0w-20	4.4	10,000 Miles
	Venza	1AR-FE	2010-2012	5w-20 or 0w-20	4.7	5,000 Miles
		1AR-FE	2013-2014	0w-20	4.7	10,000 Miles
		2GR-FE	2010-2011	5w-30	6.4	5,000 Miles
			2012-2014	0w-20	6.4	10,000 Miles
	Yaris	1NZ-FE	2010-2014	5w-30	3.9	5,000 Miles

LINK REFERENCES

This Tech Tip does not contain any link references

Expires on 02/04/2015 Ver. 2.2 09/06/2013 T Rev1