

Uneven Rear Brake Pad Wear

Service
Category Brake

Section Brake (rear)

Market USA

Toyota Supports
ASE Certification 

Applicability

YEAR(S)	MODEL(S)	ADDITIONAL INFORMATION
2009 – 2013	Corolla	
2009 – 2013	Matrix	

Introduction

Some 2009 – 2013 model year Corolla and Matrix vehicles may exhibit uneven brake pad wear on the rear disc brake pads. The vehicle may also exhibit a grinding or scraping noise due to the uneven brake pad wear. An updated rear disc brake pad kit has been developed to address this condition.

Production Change Information

This bulletin applies to vehicles produced **BEFORE** the Production Change Effective VINs shown below.

MODEL	PLANT	DRIVETRAIN	PRODUCTION CHANGE EFFECTIVE VIN
Corolla	Takaoka	FWD	JTDBU4EE#DJ112296
	TMMC		2T1BU4EE#DC028654
	TMMMS		5YEBU4EE#DP143363
Matrix	TMMC		2T1KE4EE#DC051047
			2T1KU4EE#DC037631

Warranty Information

OP CODE	DESCRIPTION	TIME	OFP	T1	T2
473061	R & R Pad Kit	0.6	04466-02210	87	19
Combo A	Opposite Side	0.3			

APPLICABLE WARRANTY

- This repair is covered under the Toyota Basic Warranty. This warranty is in effect for 36 months or 36,000 miles, whichever occurs first, from the vehicle's in-service date.
- Warranty application is limited to occurrence of the specified condition described in this bulletin.

Uneven Rear Brake Pad Wear

Parts Information

PREVIOUS PART NUMBER	CURRENT PART NUMBER	PART NAME	QTY
04466-02210 04466-02270	04466-02260	Pad Kit, Disc Brake, Rear	1

Required Tools & Equipment

SPECIAL SERVICE TOOLS (SST)	PART NUMBER	QTY
Variable Pin Wrench Set*	<u>09960-10010</u>	1
Rear Disc Brake Tool Set*	<u>09719-14020</u>	1
Companion Flange Holding Tool*	<u>09330-00021</u>	1

* Essential SST.

NOTE

Additional SSTs may be ordered by calling 1-800-933-8335.

Repair Procedure

1. Remove the rear brake pads.

Refer to the Technical Information System (TIS), applicable model and model year Repair Manual:

- 2009 / 2010 / 2011 / 2012 / 2013 Corolla:
Brake – Brake (Rear) – “Brake (Rear): Rear Brake (for Disc Type): Removal”
- 2009 / 2010 / 2011 / 2012 / 2013 Matrix:
Brake – Brake (Rear) – “Brake (Rear): Rear Brake (for Torsion Beam Type Suspension): Removal”

2. Inspect the rotor and pads.

Refer to TIS, applicable model and model year Repair Manual:

- 2009 / 2010 / 2011 / 2012 / 2013 Corolla:
Brake – Brake (Rear) – “Brake (Rear): Rear Brake (for Disc Type): Inspection”
- 2009 / 2010 / 2011 / 2012 / 2013 Matrix:
Brake – Brake (Rear) – “Brake (Rear): Rear Brake (for Torsion Beam Type Suspension): Inspection”

Uneven Rear Brake Pad Wear

Repair Procedure (Continued)

3. Install the NEW brake pads.

Refer to TIS, applicable model and model year Repair Manual:

- 2009 / 2010 / 2011 / 2012 / 2013 Corolla:
Brake – Brake (Rear) – “Brake (Rear): Rear Brake (for Disc Type): Installation”
- 2009 / 2010 / 2011 / 2012 / 2013 Matrix:
Brake – Brake (Rear) – “Brake (Rear): Rear Brake (for Torsion Beam Type Suspension): Installation”