



Technical Service Bulletin

SUBJECT:		No: TSB-15-00-001	
TECHNICAL SPECIFICATIONS – 2015 OUTLANDER SPORT: REVISED		DATE: February, 2015	
		MODEL: 2015 Outlander Sport/ RVR	
CIRCULATE TO:	<input type="checkbox"/> GENERAL MANAGER	<input checked="" type="checkbox"/> PARTS MANAGER	<input checked="" type="checkbox"/> TECHNICIAN
<input checked="" type="checkbox"/> SERVICE ADVISOR	<input checked="" type="checkbox"/> SERVICE MANAGER	<input checked="" type="checkbox"/> WARRANTY PROCESSOR	<input checked="" type="checkbox"/> SALES MANAGER

This bulletin supersedes TSB-14-00-010, issued July, 2014 to add 2.4L powertrain technical specifications. This is a complete rewrite and changes are not indicated.

2015 OUTLANDER SPORT (U.S. Models)

ENGINE	ES / SE (2WD & AWC)	2.4L ES / 2.4L GT (2WD & AWC)	TRANSMISSION RATIOS				
Type	2.0L, MIVEC inline-4	2.4L MIVEC inline-4	M/T	CVT (2.0)	CVT (2.4)		
Engine Code	4B11	4B12	CVT Mode	N/A	2.631-0.378 2.348-0.394		
Engine Block/Cylinder	Aluminum/Aluminum		1 st	3.833	2.631 2.349		
Displacement (cu. in./cc)	122/1998	144/2360	2 nd	1.913	1.440 1.517		
Bore x Stroke (in./mm)	3.4 x 3.4 / 86.0 x 86.0	3.5 x 3.8 / 88 x 97	3 rd	1.333	1.165 1.105		
Compression Ratio	10:1	10.5:1	4 th	1.028	0.906 0.857		
Horsepower @ RPM	148 bhp @ 6000	168 bhp @ 6000	5 th	0.82	0.680 0.621		
Torque @ RPM (lb-ft)	145 lb/ft @ 4200	167 lb/ft @ 4100	6 th	N/A	0.499 0.446		
Cylinder Head Valve Train	DOHC 16V	DOHC 16V	Rev	3.583	1.960 1.750		
Redline	6500 RPM		Final Drive	4.235	6.026 6.466		
Fuel System	Electronically Controlled Multi-Point Fuel Injection		RACK & PINION POWER ASSIST STEERING				
Engine Oil Capacity (w/o filter)	CVT- 4.5 L (4.3 qt.)	4.5 L (4.2 qt.)	Type:	Electric power assisted rack & pinion			
Engine Oil Type	0W-20 Minimum: API Service Standard SN (ILSAC certification)		Ratio	43.69 mm/rev			
SUSPENSION			Turns Lock - Lock	3.3			
Front	Independent MacPherson strut, coil springs, 22 mm stabilizer bar		Turn. Cir C-C (ft/m)	34.8/10.6			
Rear	Multi-link, coil springs 16 mm stabilizer bar (S-AWC – 19 mm)		ELECTRICAL SYSTEM				
BRAKES			Battery	Group 35-118			
Frt. Ventilated Disc Diameter	11.6" / 294mm		Alternator	530 CCA 130 amp			
Rear Solid Disc Diameter	11.9" / 302mm		WEIGHTS (lbs./kg.)				
Total swept area (sq. in.)	424		GVWR (All)	4343 (1970)			
Anti-Lock Brake System	4-sensor, 4-channel with EBD		Curb wt.	2WD	AWC		
EXTERIOR DIMENSIONS (in. / mm)			2.0 ES (CVT)	3098 (1405)	3241 (1470)		
Wheelbase	105.1 / 2670		2.0 ES (M/T)	3021 (1370)	N/A		
Length	169.1 / 4295		2.0 SE	3131 (1420)	3274 (1485)		
Width	69.7 / 1770		2.4 ES	3109 (1410)	3252 (1475)		
Height	64.2 / 1630 (64.6/1640 w/roof rails)		2.4 GT	3142 (1425)	3285 (1490)		
Front Tread Width	60.0 / 1525		Weight Distribution				
Rear Tread Width	60.0 / 1525		CVT (M/T)	60/40 (59/41)	59/41 (N/A)		
Min. Ground Clearance	8.5 / 215		WHEELS & TIRES				
INTERIOR DIMENSIONS (cu. ft.)			Wheels	18X7 J Alloy			
Interior Volume	119.2 (117.3 w/panoramic roof)		Tires	P225/55R18 97H - NEXEN			
Passenger	97.5 (95.6 w/panoramic roof)		Spare Tire	T155/90D16			
Cargo capacity behind frt. seat	49.5 (48.8 w/panoramic roof)		FUEL TANK CAPACITY (gal./l.)				
Cargo capacity behind rear seat	21.7 (20.1 w/subwoofer)		15.3 / 58 (2WD)	15.8 / 60 (AWC)			
PASSENGER SPACE (in/mm)			EPA FUEL ECONOMY (m.p.g.)				
Headroom (w/ Panoramic)	Front	Rear		City	Hwy	Comb.	
Shoulder Room	39.4 (38.9) / 1000 (988)	37.9 (36.8) / 962.7 (934.7)	2.0 ES (M/T)	25 (24)	32 (30)	28 (26)	
Hip Room	56.2 / 1428	55.5 / 1410	2.0 ES AWC	24	30	27	
Leg Room (MAX)	52.1 / 1324	51.6 / 1310	2.0 SE 2WD	25	32	28	
Max. Passenger Capacity	41.6 / 1056	36.3 / 921	2.0 SE AWC	24	30	27	
WARRANTIES - U.S. shown - Coverage may vary according to terms in effect at time of first sale			2.4 ES 2WD	23	28	25	
	Basic	Powertrain	Anti-corrosion	2.4 ES AWC	23	26	24
Yrs	5	10	7	2.4 GT 2WD	23	28	25
Miles	60,000	100,000	100,000	2.4 GT AWC	23	26	24
				See individual statement for CA & Fed. coverage			
				*U.S. coverage shown. Coverage may vary according to terms in effect at the time of purchase			

Copyright 2015, Mitsubishi Motors North America, Inc.

The information contained in this bulletin is subject to change. For the latest version of this document, go to the Mitsubishi Dealer Link, MEDIC, or the Mitsubishi Service Information website (www.mitsubishitechinfo.com)

(4249)